

AMI REINFORCED ALUMINUM TAPE (Foil Scrim Kraft Tape)

USES

- Closure System for Fiber Glass & Mineral Wool Insulation System that is faced with foil.
- Seal seams and Joints on aluminum faced fiber glass duct board.

COLORS

AMI REINFORCED ALUMINUM TAPE is available in silver metallic color only.

SLITT ROLLS & JUMBO ROLLS

Width and length are available on request.

PACKING

AMI REINFORCED ALUMINUM TAPE is available in 16 and 24 standard rolls per carton. 1200 mm width x 900 meters length jumbo roll.

STORAGE CONDITION

Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before twelve (12) months when stored at 25°C with 50% Relative Humidity.

DESCRIPTION

AMI REINFORCED ALUMINUM TAPE is a pressure sensitive rubber based adhesive with foil, scrim Kraft reinforced and self-wound in release liner.

TYPICAL PROPERTIES

Test Method	Properties	Unit	Specification
Lab Test	Color	Visually	Silver metallic
Lab test	Backing	n/a	Foil Scrimmed Kraft
ASTM D 3652	Adhesive	n/a	Rubber based
ASTM D 3652	Total Thickness	Micron	180±10
ASTM D 3330	Peel strength	N/25mm	≥10
ASTM D 3759	Tensile Strength	N/25mm	≥50
ASTM D 3121	Rolling ball tack	mm	≤100

**Information on this data sheet is subject to change without prior notice and should not be used for writing specifications*

For additional information on specific applications, contact AL MUQARRAM INSULATION INDUSTRY L.L.C.

SHIPPING LIMITATIONS

None