

## AMI PE 45 PROTECTION TAPE

### USES

- Smooth Aluminum surfaces
- Polished SS surfaces
- PVC(Doors & Frames)
- Glass & Mirror finish surfaces

### COLORS

**AMI PE 45 PROTECTION TAPE** is available in Transparent.

### PACKING

**AMI PE 45 PROTECTION TAPE** is available in two rolls per carton of 1000/1250 mm width x 65 ,70 & 100 yards.

Other sizes are available on Request

### GENERAL INFORMATION

Before application the surface must be free from Oil, Fat, Dust & Solvents.

Best to apply at room temperature between >15°C and < 55°C.

### STORAGE CONDITION

Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before six (6) months when stored at 30°C with 50% Relative Humidity.

### SHIPPING LIMITATIONS

None

### DESCRIPTION

**AMI PE 45 PROTECTION TAPE** is a polyethylene protection tape having low peel acrylic emulsion pressure sensitive adhesive system to provide temporary protection to surface during mechanical process, storage and transportation.

It does not leave any adhere residue after peeling off from the applied surface.

### TYPICAL PROPERTIES

Test Method	Properties	Unit	Specification
Lab Test	Color	Visually	Transparent
Lab test	Backing	n/a	PE film
ASTM D 3652	Adhesive	n/a	Cross linked acrylic emulsion
ASTM D 3652	Total Thickness	Micron	45±3
ASTM D 3330	Peel strength	N/25mm	≥1
ASTM D 3759	Tensile Strength	N/25mm	≥15
ASTM D 3121	Rolling ball tack	mm	n/a
ASTM D 3654	Holding power	Hour	n/a

*\*Information on this data sheet is subject to change without prior notice and should not be used for writing specifications*

*For additional information on specific applications, contact AL MUQARRAM INSULATION INDUSTRY L.L.C.*

Made in U.A.E

Al-Muqarram Insulation Materials Industry L.L.C.

P.O.Box: 24756, Sharjah. U.A.E

Phone: + 971 6 5353796, Fax: + 971 6 5353964

Mail: info@muqarram.com, sales@muqarram.com

Website: [www.muqarram.com](http://www.muqarram.com)