

AMI PE 55 PROTECTION TAPE

USES

- Aluminum panel/ profile
- Construction area
- Plastic windows & door
- Glossy surface.

COLORS

AMI PE 55 PROTECTION TAPE is available in black & black, black & white, transparent. These tapes can be customized with any imprint of your company's name, logo and telephone number.

PACKING

AMI PE 55 PROTECTION TAPE is available in two rolls per carton and 1000/1250 mm x 65 yards.

STORAGE CONDITION

Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before twelve (12) months when stored at 25°C with 50% Relative Humidity.

SHIPPING LIMITATIONS

None

DESCRIPTION

AMI PE 55 PROTECTION TAPE is a polyethylene protection tape having low peel acrylic emulsion, pressure sensitive adhesive system to provide temporary protection of surface during mechanical process, storage and transportation.

It does not leave any adhere residue after peeling off from the applied surface.

TYPICAL PROPERTIES

Test Method	Properties	Unit	Specification
Lab Test	Color	Visually	Black & White
Lab test	Backing	n/a	PE film
ASTM D 3652	Adhesive	n/a	Cross linked acrylic emulsion
ASTM D 3652	Total Thickness	Micron	55±3
ASTM D 3330	Peel strength	N/25mm	≥1.25
ASTM D 3759	Tensile Strength	N/25mm	≥30
ASTM D 3121	Rolling ball tack	mm	n/a
ASTM D 3654	Holding power	Hour	n/a

**Information on this data sheet is subject to change without prior notice and should not be used for writing specifications*

For additional information on specific applications, contact AL MUQARRAM INSULATION INDUSTRY L.L.C.