

## AMI 38 BOPP PACKAGING TAPES

### USES

- General purpose packing
- Splicing and sealing
- Mounting
- Bundling and holding laminations

### COLORS

**AMI 38 BOPP PACKAGING TAPES** is available in Clear, and Brown. Other colors are available upon request.

### SLITT ROLLS & JUMBO ROLLS

Width and length are available on request.

### PACKING

**AMI 38 BOPP PACKAGING TAPES** are available in 36 and 72 standard rolls per carton. 1280mm width x 4000 meter length jumbo roll.

### STORAGE CONDITION

Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before twelve (12) months when stored at 25°C with 50% Relative Humidity.

### DESCRIPTION

**AMI 38 BOPP PACKAGING TAPE** Biaxially-oriented polypropylene (**BOPP**) coated with acrylic emulsion pressure sensitive adhesive of high tensile strength, excellent adhesion and flexibility.

### TYPICAL PROPERTIES

Test Method	Properties	Unit	Specification
Lab Test	Color	Visually	Clear and Brown
Lab test	Backing	BOPP film	23±1 Micron
ASTM D 3652	Adhesive	Micron	15±1
ASTM D 3652	Total Thickness	Micron	38±1
ASTM D 3330	Peel strength	N/25mm	≥3
ASTM D 3759	Tensile Strength	N/25mm	50
ASTM D 3121	Rolling ball tack	mm	≤150
ASTM D 3654	Holding power	Hour	≥ 10

*\*Information on this data sheet is subject to change without prior notice and should not be used for writing specifications*

*For additional information on specific applications, contact AL MUQARRAM INSULATION INDUSTRY L.L.C.*

### SHIPPING LIMITATIONS

None