

DOLPHIN 300 ALUMINUM FOIL TAPE

USES

- General purpose holding, patching, sealing.
- Reflect heat & light away from sensitive area.
- Coupling and sealing pipe joints in ventilation, air condition and refrigeration systems.

COLORS

DOLPHIN 300 ALUMINUM FOIL TAPE is available in silver metallic color only.

SLITT ROLLS & JUMBO ROLLS

Width and length are available on request.

PACKING

DOLPHIN 300 ALUMINUM FOIL TAPE is available in 16 and 24 standard rolls per carton. 1200 mm width x 1600 meters length jumbo roll.

STORAGE CONDITION

Tapes are to be stored in a cool, dry area away from direct sunlight, air conditioner and other heat sources. Tapes should be used within twelve (12) months from shipment. For best performance apply the tape on clean, dry, dust & oil free surfaces between 25 to 45°C

SHIPPING LIMITATIONS

None

DESCRIPTION

DOLPHIN 300 ALUMINUM FOIL TAPE is a soft aluminum foil coated with Rubber Resin pressure sensitive adhesive of high shear and excellent adhesion and self-wound on release liner.

TYPICAL PROPERTIES

Test Method	Properties	Unit	Specification
Lab Test	Color	Visually	Silver metallic
Lab test	Backing		Foil
ASTM D 3652	Adhesive	Micron	30±5
ASTM D 3652	Total Thickness	Micron	70 ±5
ASTM D 3330	Peel strength	N/25 mm	≥20
ASTM D 3759	Tensile Strength	N/25 mm	≥30
ASTM D 3121	Rolling ball tack	mm	≤80

**Information on this data sheet is subject to change without prior notice and should not be used for writing specifications*

For additional information on specific applications, contact AL MUQARRAM INSULATION INDUSTRY L.L.C.