



DOLPHIN AM-40 ANTI RUST LUBRICANT

DOLPHIN AM-40 ANTI RUST LUBRICANT provides better quality lubrication and long term rust protection to all metals subjected to rust and corrosion. It is an outstanding solution for extending the life of metal to metal sliding/rotating surfaces.

DOLPHIN AM-40 ANTI RUST LUBRICANT can infiltrate the areas of rust in short time. Moreover, it can minimize the noise created by moving metal parts to zero. It also displaces the moisture to reinstate the equipment such as spark plugs, engines and power tools.



TYPICAL PROPERTIES

Properties	Specifications
Appearance	Transparent Liquid
Odor	Characteristic
Density @ 25°C	0.81 ± 0.02 g/cm ³
Solubility in Water	Insoluble
Flash Point	45°C

Note:

** Information on this data sheet is subject to change without prior notice and should not be used for writing specifications.*

KEY FEATURES

- Protect tools and machinery over a long period of downtime.
- Preserve engine, piston and components from atmospheric rusting.
- It does not require cleaning before using equipment.

PERFORMANCE

Average Film Thickness	4 – 12 µm
Dry to Touch Time	Not applicable
Reapplication Period Outdoors	6 – 12 months
Reapplication Period Indoors	2 years

DIRECTIONS FOR USE

- Shake can before spraying.
- Spray evenly on the desired surface by making sure all the surface is coated for maximum protection.
- Cleaning of Lube film is not required before startup.

**DOLPHIN AM-40 ANTI RUST LUBRICANT****PACKAGING**

DOLPHIN AM-40 ANTI RUST LUBRICANT is available in:

- 220 ML (24 pcs/carton)
- 400 ML (12pcs/carton)
- 480 ML (24pcs/carton)

STORAGE AND SHELF LIFE

Store in a cool, dry location in unopened containers at temperature below 50°C. Do not place in direct sunlight or nearby any heat and flame source. Do not expose to temperature exceeding 50°C.

DOLPHIN AM-40 ANTI RUST LUBRICANT has a shelf life of 36 months from date of manufacturing.

HANDLING PRECAUTIONS

Contents extremely flammable. Do not smoke while spraying. Do not use near open flames. Do not puncture or incinerate even after use. Exposure to high temperatures may cause can to burst. Keep away from all live electrical sources including battery terminals, electrical panels and other electrical components. For safe handling information, refer to the Material Safety Data Sheet of this product.

KEEP OUT OF REACH OF CHILDREN • KEEP CONTAINER TIGHTLY CLOSED • FOR INDUSTRIAL & PROFESSIONAL USE

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

AL MUQARRAM INSULATION MATERIALS INDUSTRY, LLC

P.O. Box: 24753, Sharjah, UAE

Phone: + 971 6 5353796

Fax: +971 6 5353964

E-mail: info@muqarram.com, sales@muqarram.com