



DOLPHIN RADIATOR COOLANT

DOLPHIN RADIATOR COOLANT is the premium blend of glycols, rust Inhibitors and other performance enhancers for achieving optimum engine temperatures and extending the service life.

TYPICAL PROPERTIES



Properties	Specifications
Basis	Glycol and DM Water
Color	Greenish
Density	1.10 ± 0.01 g/cm ³
pH	8 – 9

Note:

** Information on this data sheet is subject to change without prior notice and should not be used for writing specifications.*

KEY FEATURES

- Ready to use.
- Formulated with special additives to increase the boiling point of product.
- Prevent rust, corrosion and buildup of scale.
- Can be used in radiators made up from different metals.
- Will not affect gasket and hoses.

TYPICAL APPLICATIONS

DOLPHIN RADIATOR COOLANT can be used in all type of modern radiators operating at high temperatures using various metals in their construction.

DIRECTIONS FOR USE

- When engine is cold, flush out the cooling system by opening the drain plugs.
- Open the radiator cap. Using a hose with running water, let the water enter into the system and run continuously until water coming out of drain is clear.
- Fasten all drain plugs.
- Fill the system with 100% Dolphin Radiator Coolant.
- Run engine and check for leaks.
- Replace Dolphin Radiator Coolant after every 6,000-8,000 kms.

PACKAGING

DOLPHIN RADIATOR COOLANT is available in 1 gallon container with 6 containers per packing.

STORAGE AND SHELF LIFE

Store in a cool, dry location in unopened containers at temperature below 50°C. Do not place in direct sunlight or nearby any heat and flame source.

DOLPHIN RADIATOR COOLANT has a shelf life of 36 months from date of manufacturing.

**DOLPHIN RADIATOR COOLANT****HANDLING
PRECAUTIONS**

DOLPHIN RADIATOR COOLANT is unlikely to present any health and safety hazard when used in the recommended application and good standard of hygiene. Use gloves while pouring the coolant. Avoid skin contact. If coolant contact skin wash with water and soap immediately. For safe handling information, refer to the Material Safety Data Sheet of this product.

KEEP OUT OF REACH OF CHILDREN • KEEP CONTAINER TIGHTLY CLOSED • FOR INDUSTRIAL & PROFESSIONAL USE

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

AL MUQARRAM INSULATION MATERIALS INDUSTRY, LLC

P.O. Box: 24753, Sharjah, UAE

Phone: + 971 6 5353796

Fax: +971 6 5353964

E-mail: info@muqarram.com, sales@muqarram.com