



DOLPHIN AEROSOL SPRAY PAINT

DOLPHIN AEROSOL SPRAY PAINT acrylic spray paint is made from 100 % Acrylic resin and CFC free advanced technology specially formulated for decorative and protective purposes. Its film finish has excellent hardness with excellent weather resistance making it suitable both for interior or exterior applications.



TYPICAL PROPERTIES

Properties	Specifications
Composition	Pure Acrylic Polymer + Pigment + Solvents + Standard CFC Free Gas
Specific Gravity	0.90 ± 0.05 g/cm ³
Viscosity on Zahn Cup	30.00 ± 5 sec
Auto Ignition Temp.	420°C
Flash Point	<10°C
VOC Contents	677 g/L

Note:

** Information on this data sheet is subject to change without prior notice and should not be used for writing specifications.*

KEY FEATURES

- Good leveling
- High coverage
- High spray rate
- Fast drying
- Strong adhesion
- Rich color
- High gloss

TYPICAL APPLICATIONS

It can be used widely in interior and exterior surfaces like in finishing and mending of metal, wood, glass, leather, ceramics and plastics.

DIRECTIONS FOR USE

- Clean the surface if it is dusty, oily or greasy. If rusted sand those areas prior to spray paint application.
- Check the actuator and clean it, if necessary.
- Shake well before using the paint.
- Spray the paint on rough surface once to judge the internal pressure.
- Spray exactly parallel from the start till end in to and fro motion.
- The minimum distance of 12" or 30 cm should be kept between the can and the substrate.

PACKAGING

DOLPHIN AEROSOL SPRAY PAINT can has a volume of 400 ml with 12 cans packed in each carton.



DOLPHIN AEROSOL SPRAY PAINT

COLOR SHADES

- Standard colors
- Special color
- Matt shade
- Metallic Shade
- Fluorescent shade

STORAGE AND SHELF LIFE

Store in a cool, dry location in unopened containers below 25°C. Do not place in direct sunlight or nearby any heat, sparks, and flame source.

DOLPHIN AEROSOL SPRAY PAINT has a shelf life of 36 months from date of manufacturing. Storage outside specified parameters may reduce the shelf life. A maximum of 6.7 ft. height should be kept of the pallet containing Spray paint cartons.

HANDLING PRECAUTIONS

Do not use near flames, sparks, direct sunlight, heat and etc. Pressurized container. Do not expose to heat beyond 50°C. Do not puncture and incinerate the can.

For safe handling information, refer to the Material Safety Data Sheet of this product.

KEEP OUT OF REACH OF CHILDREN • KEEP CONTAINER TIGHTLY CLOSED • FOR INDUSTRIAL & PROFESSIONAL USE

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

AL MUQARRAM INSULATION MATERIALS INDUSTRY, LLC

P.O. Box: 24753, Sharjah, UAE
 Phone: + 971 6 5353796
 Fax: +971 6 5353964
 E-mail: info@muqarram.com, sales@muqarram.com