

HI STICK 40 BOPP PACKAGING TAPES

USES

- General purpose packing
- Splicing and sealing
- Mounting
- Bundling and holding laminations

COLORS

HI STICK 40 BOPP PACKAGING TAPES is available in Clear, and Brown. Other colors are available upon request.

SLITT ROLLS & JUMBO ROLLS

Width and length are available on request.

PACKING

HI STICK 40 BOPP PACKAGING TAPES are available in 36 and 72 standard rolls per carton. 1280mm width x 4000 meter length jumbo roll.

STORAGE CONDITION

Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before twelve (12) months when stored at 25°C with 50% Relative Humidity.

DESCRIPTION

HI STICK 40 BOPP PACKAGING TAPE Biaxially-oriented polypropylene (**BOPP**) coated with acrylic emulsion pressure sensitive adhesive of high tensile strength, excellent adhesion and flexibility.

TYPICAL PROPERTIES

Test Method	Properties	Unit	Specification
Lab Test	Color	Visually	Clear and Brown
Lab test	Backing	BOPP film	23±1 Micron
ASTM D 3652	Adhesive	Micron	17±1
ASTM D 3652	Total Thickness	Micron	40±1
ASTM D 3330	Peel strength	N/25mm	≥3
ASTM D 3759	Tensile Strength	N/25mm	50
ASTM D 3121	Rolling ball tack	mm	≤150
ASTM D 3654	Holding power	Hour	≥ 10

**Information on this data sheet is subject to change without prior notice and should not be used for writing specifications*

For additional information on specific applications, contact AL MUQARRAM INSULATION INDUSTRY L.L.C.

SHIPPING LIMITATIONS

None