



AMI 40 MIC BOPP PACKAGING TAPES

AMI 40 Mic BOPP Packaging Tape comprises of a Biaxially – Oriented Poly Propylene (BOPP) film coated with acrylic emulsion pressure sensitive adhesive of high tensile strength, excellent adhesion and flexibility.

TECHNICAL PROPERTIES

Properties	Test Method	Unit	Specification
Color	Lab Test	Visual	Clear and Brown
Backing	Lab Test	BOPP film	23 ± 1 Micron
Adhesive	ASTM D 3652	Micron	17 ± 1
Total Thickness	ASTM D 3652	Micron	40 ± 1
Peel Strength	ASTM D 3330	N/25mm	≥ 3
Tensile Strength	ASTM D 3759	N/25mm	50
Rolling Ball Tack	ASTM D 3121	mm	≤ 150
Holding Power	ASTM D 3654	Hours	> 10



Note:

** Information on this data sheet is subject to change without prior notice and should not be used for writing specifications.*

** For additional information on specific applications, contact Al Muqarram Insulation Industry L.L.C.*

TYPICAL USES

- Splicing and sealing
- Mounting
- General purpose packaging
- Bundling & holding laminations

COLORS

AMI 40 Mic BOPP Packaging Tapes is available in Clear and Brown colors. Other colors are available upon request.

**Special color orders may require lead time and minimum order quantities.*

SLIT ROLLS & JUMBO ROLLS

Width and length are available on request.

PACKING

AMI 40 Mic BOPP Packaging Tapes are available in 36 and 72 standard rolls per carton. Each jumbo roll has a 1280 mm width x 4000 Meters length.

STORAGE CONDITION

Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes should be used within twelve (12) months when stored at 25°C with 50% Relative Humidity.

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

AL MUQARRAM INSULATION MATERIALS INDUSTRY, LLC

P.O. Box: 24753, Sharjah, UAE

Phone: + 971 6 5353796

Fax: +971 6 5353964

E-mail: info@muqarram.com, sales@muqarram.com