



AMI HIGH TEMPERATURE 80 MASKING TAPE

AMI HT 80 Masking Tape is a yellow colored crepe paper coated with rubber based adhesives of high shear strength and excellent adhesion.

TECHNICAL PROPERTIES



Properties	Test Method	Unit	Specification
Color	Lab Test	Visually	Yellow
Backing	Lab Test	n/a	Crepe paper
Adhesive	Lab Test	n/a	Rubber based
Total Thickness	ASTM D 3652	Micron	135 + 10
Peel Strength	ASTM D 3330	N/25mm	≥ 4
Tensile Strength	ASTM D 3759	N/25mm	≥ 50
Rolling Ball Tack	ASTM D 3121	mm	≤ 110
Holding Power	ASTM D 3654	Hour	≥ 5
Max. Temp. Resistance	Lab Test	°C	80

Note:

** Information on this data sheet is subject to change without prior notice and should not be used for writing specifications.*

** For additional information on specific applications, contact Al Muqarram Insulation Industry L.L.C.*

TYPICAL USES

- General purpose packing
- Bundling, Labeling, Paint masking
- For paint masking at medium temperature

COLORS AMI HT 80 Masking Tape is available in yellow color only.

SLIT ROLLS & JUMBO ROLLS Width and length are available on request.

PACKING AMI HT 80 Masking Tape is available in 16 and 24 standard rolls per carton. 1575 mm width x 1850 meters length jumbo roll.

STORAGE CONDITION Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before twelve (12) months when stored at 25°C with 50% Relative Humidity.

SHIPPING LIMITATIONS None

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

AL MUQARRAM INSULATION MATERIALS INDUSTRY, LLC

P.O. Box: 24753, Sharjah, UAE

Phone: + 971 6 5353796

Fax: +971 6 5353964

E-mail: info@muqarram.com, sales@muqarram.com