



DOLPHIN DOUBLE SIDED FOAM TAPE

Dolphin Double Sided Foam Tape is Irradiated Cross-linked Polyethylene Foam coated with solvent based acrylic pressure sensitive adhesive of high shear and excellent adhesion and self-wound on a double side release liner.

TECHNICAL PROPERTIES

Properties	Test Method	Unit	Specification
Color	Lab Test	Visually	Black / White foam
Backing	Lab test	n/a	Cross-linked Polyethylene Foam
Total Thickness	ASTM D 3652	mm	1 ± 0.05
Peel Strength (1st Side)	ASTM D 3330	N/25mm	≥ 12
Peel Strength (2nd Side)	ASTM D 3330	N/25mm	≥ 10
Roll Ball Tack	ASTM D 3121	mm	≤ 90
Shear Strength	ASTM D 3654	Hours	≥ 10

Note:

** Information on this data sheet is subject to change without prior notice and should not be used for writing specifications.*

** For additional information on specific applications, contact Al Muqarram Insulation Industry L.L.C.*

TYPICAL USES

- Indoor & outdoor bonding and mounting
- Name plates, car number plates and mounting mirrors
- Noise / vibration control applications

COLORS	Dolphin Double Sided Foam Tape is available in Black & White color.
SLIT ROLLS AND JUMBO ROLLS	Width and length are available on request.
PACKING	Dolphin Double Sided Foam Tape is available in 24 mm width x 25 Mtrs Length 48 rolls per carton. 48 mm width x 25 Mtrs length 24 rolls per carton. Other sizes available on request.
STORAGE CONDITION	Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before twelve (12) months when stored at 30°C with 50% Relative Humidity. For best performance apply the tape on clean, dry, dust & oil free surfaces between 25 to 45°C.
SHIPPING LIMITATIONS	None

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

AL MUQARRAM INSULATION MATERIALS INDUSTRY, LLC
P.O. Box: 24753, Sharjah, UAE
Phone: + 971 6 5353796
Fax: +971 6 5353964
E-mail: info@muqarram.com, sales@muqarram.com