



## AMI Reinforced Aluminum Foil Tape (FSK Tape)

**AMI Reinforced Aluminum Foil Tape (FSK Tape)** is a hot melt pressure sensitive adhesive based tape with foil, scrim, kraft self-wound on release liner.



### TECHNICAL PROPERTIES

Properties	Test Method	Unit	Specification
<b>Color</b>	Lab Test	Visually	Silver metallic
<b>Backing</b>	Lab test	n/a	Foil scrim kraft
<b>Adhesive</b>	ASTM D 3652	n/a	Rubber Resin
<b>Total Thickness</b>	ASTM D 3652	Micron	180 ± 10
<b>Peel Strength</b>	ASTM D 3330	N/25mm	≥ 10
<b>Tensile Strength</b>	ASTM D 3759	N/25mm	≥ 50
<b>Rolling Ball Tack</b>	ASTM D 3121	mm	≤ 100

*Note:*

*\* Information on this data sheet is subject to change without prior notice and should not be used for writing specifications.*

*\* For additional information on specific applications, contact Al Muqarram Insulation Industry L.L.C.*

### TYPICAL USES

- Closure System for Fiber Glass & Mineral Wool Insulation System that is faced with foil.
- Seal seams and Joints on aluminum faced fiber glass duct board.

<b>COLORS</b>	<b>AMI Reinforced Aluminum Foil Tape</b> is available in silver metallic color only.
<b>SLIT ROLLS &amp; JUMBO ROLLS</b>	Width and length are available on request.
<b>PACKING</b>	<b>AMI Reinforced Aluminum Foil Tape</b> is available in 16 and 24 standard rolls per carton. 1200 mm width x 900 meters length jumbo roll.
<b>STORAGE CONDITION</b>	Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before twelve (12) months when stored at 25°C with 50% Relative Humidity. For best performance apply the tape on clean, dry, dust & oil free surfaces between 25 to 45°C.
<b>SHIPPING LIMITATIONS</b>	None

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

**AL MUQARRAM INSULATION MATERIALS INDUSTRY, LLC**

P.O. Box: 24753, Sharjah, UAE

Phone: + 971 6 5353796

Fax: +971 6 5353964

E-mail: info@muqarram.com, sales@muqarram.com