




AMI PE 50 SURFACE PROTECTION TAPE

AMI PE 50 Mic Protection Tape is a polyethylene protection tape having low peel acrylic emulsion pressure sensitive adhesive system to provide temporary protection to surface during mechanical process, storage and transportation. It does not leave any adhere residue after peeling off from the applied surface.



TECHNICAL PROPERTIES

Properties	Test Method	Unit	Specification
Color	Lab Test	Visually	Blue/Transparent
Backing	Lab test	n/a	PE film
Adhesive	ASTM D 3652	n/a	Cross linked acrylic emulsion
Total Thickness	ASTM D 3652	Micron	50 ± 3
Peel Strength	ASTM D 3330	N/25mm	≥ 1
Tensile Strength	ASTM D 3759	N/25mm	≥ 15
Rolling Ball Tack	ASTM D 3121	mm	n/a

Note:

- * Information on this data sheet is subject to change without prior notice and should not be used for writing specifications.
- * For additional information on specific applications, contact Al Muqarram Insulation Industry L.L.C.

TYPICAL USES

- Polished SS surfaces
- PVC (Doors & Frames)
- Glass & Mirror finish surfaces.

COLORS

AMI PE 50 Mic Protection Tape is available in Transparent

PACKING

AMI PE 50 Mic Protection Tape is available in two rolls per carton of 1000/1250 mm width x 65, 70 & 100 yards. Other sizes are available on Request.

STORAGE CONDITION

Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. PE Tapes should be used before 8 (eight) months when stored at 30°C with 50% Relative Humidity. Before application the surface must be free from Oil, Fat, Dust and Solvents. For the best performance, apply the tapes at room temperature between 15°C and 45°C.

SHIPPING LIMITATIONS

None

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

AL MUQARRAM INSULATION MATERIALS INDUSTRY, LLC
P.O. Box: 24753, Sharjah, UAE
Phone: + 971 6 5353796
Fax: +971 6 5353964
E-mail: info@muqarram.com, sales@muqarram.com