



## AMI PVC PIPE WRAPPING TAPE

**PVC Pipe Wrapping Tape** is Poly Vinyl Chloride film coated with Synthetic Rubber pressure sensitive adhesive with an excellent peel strength, anti-corrosiveness & moisture resistance.

### TECHNICAL PROPERTIES



Properties	Test Method	Unit	Specification
Color	Lab Test	Visual	Black
Total Thickness	ASTM D 3652	Micron	130 ± 10
Peel Strength	ASTM D 3330	N/25mm	≥ 2
Tensile Strength	ASTM D 3759	N/25mm	≥ 20
Roll Ball Tack	ASTM D 3121	mm	≤ 100
Holding Power	ASTM D 3654	Hour	NA
Temperature Resistance (30 min)	Lab test	°C	70 °C max
Application Temperature	Lab test	°C	10 °C to 55 °C

*Note:*

*\* Information on this data sheet is subject to change without prior notice and should not be used for writing specifications.*

*\* For additional information on specific applications, contact Al Muqarram Insulation Industry L.L.C.*

### TYPICAL USES

- Air condition duct wrapping
- Pipeline Protection
- Moisture Proofing

<b>COLORS</b>	PVC Pipe Wrapping Tape is available in Black Color only.
<b>SLIT ROLLS</b>	Width and length are available on request
<b>PACKING</b>	PVC Pipe Wrapping Tape is available in 60 rolls per carton.
<b>STORAGE CONDITION</b>	Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before six (6) months when stored at 25°C with 50% Relative Humidity.
<b>SHIPPING LIMITATIONS</b>	None

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

**AL MUQARRAM INSULATION MATERIALS INDUSTRY, LLC**

P.O. Box: 24753, Sharjah, UAE

Phone: + 971 6 5353796

Fax: +971 6 5353964

E-mail: info@muqarram.com, sales@muqarram.com