

TECHNICAL DATA SHEET

DOLPHIN MDF Bond Kit						
Revision Date : 25 th April 2023	Revision No. 1		Number of Pages: 2			
PRODUCT DESCRIPTION						
Dolphin Power Bond MDF KIT is a colorless, fast curing solvent-based Cyanoacrylate Adhesive & Aerosol activator. It has superior bonding strength and is specially used to bond porous substrates with uneven nature.						
TECHNICAL PROPERTIES FOR ADHESIV	E					
	TECHNICAL PROPERTIES FOR ADHESIVE					
	Chemical Base: Ethyl-2-Cyanoacrylate					
	Properties	Test Method	Unit	Specification		
	Colour	Visual	-	Transparent		
	Density	ASTM D1475	g/cm3	1.05		
	Viscosity,	ASTM D 2196 - 10	mPa- s	1.2 – 1.5		
	Cure Time	Lab Test	minutes	3 - 5		
	Cured Sample Properties					
	Service Temperature	-	°C	10 to + 80		
Dolphin	Application Temperature	-	°C	10 to 45		
WORLD-CLASS CHEMICALS	TECHNICAL PROPERTIES FOR ACTIVATOR (AEROSOL) Chemical Base: N, N Dimethyl-P-Toluidine + Solvents mixture					
	Colour	Visual	· _	Colourless Liquid		
POWER	Density	ASTM D1475	g/cm3	0.78		
	Service Temperature		°C	5 to 60+		
			C			
PUNER	Bonding Test	Bonding Time (Timer)	Unit	Results		
	Wood	3 to 10	Sec	4		
	Marble	5 to 10	Sec	5		
	Glass	5 to 10	Sec	6		
	Plastic	3 to 10	Sec	5		
	Marble Vs Wood	3 to 10	Sec	5		
	Tensile Strength	200	kg/cm2	200+		
	Note: * Curing time may vary depending on climatic condition during application. * Information on this data sheet is subject to change without prior notice and should not be used for writing specifications					

AMI | TDS | info@muqarram.com



Head Office ♥ P.O. Box 24756, Sharjah, U.A.E. ♦ +971 6 535 3796 ■ info@muqarram.com ♥ www.muqarram.com





TYPICAL USES		KEY FEATURES	
 Interior application Excellent bonding of metal to Bonding with metal to wood Good bonding in broken cera Construction – Timber applic Excellent structural adhesive Used for fixing and repairing 	, wood to wood. amic cups, glass cation e	 Excellent Adhesion No Shrinkage Non-corrosive. DIY Product. 	
DIRECTIONS FOR USE	 The substrates should be clean, dry and grease free. Spray the activator on the first substrate from safer distance. Wait for 5 seconds. Apply 2-3 drops Cyanoacrylate adhesive to the second substrate. Assemble and hold the two substrates tightly to achieve the instant bonding. 		
PACKAGING	 Dolphin MDF Kit is available in: Activator 400 ML & Glue 100g (25 pcs/carton) Activator 200 ML & Glue 50g (24 pcs/carton) Activator 155 ML & Glue 30g (24 pcs/carton) 		
STORAGE AND SHELF LIFE	Shelf life for activator- 24 months & Shelf Life for CA Glue-12 months if stored below 25 °C in an unopened container. Temperature is a critical factor in storing this material, hence material should must be kept below 25 °Stacking of 5.4 feet should be done in the warehouse.		
HANDLING PRECAUTIONS	 Until use, cyanoacrylate should be kept in sealed container. Avoid exposure to light and heat. Cyanoacrylate can bond to skin within seconds. Can cause serious damage to skin and eyes. It will become hard if the container is not sealed properly. Do not throw the activator in fire. Highly flammable! Content is under pressure in Activator can. For safe handling information, refer to the Material Safety Data Sheet of this product.		

Keep out of reach of children • Keep container tightly closed • For industrial & professional use • The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

TDS | info@muqarram.com AMI



Head Office 💡 P.O. Box 24756, Sharjah, U.A.E. 🌜 +971 6 535 3796 Sinfo@muqarram.com 🖲 www.muqarram.com



ŲAE صنع في الإمار<mark>ات</mark> MADE IN UAE