

TECHNICAL DATA SHEET

AMI PVC PIPE WRAPPING TAPE

Revision Date : 12 Nov 2019

Revision No. 1

Number of Pages : 1

PRODUCT DESCRIPTION

AMI PVC Pipe Wrapping Tape is Polyvinylchloride film coated with Synthetic Rubber pressure-sensitive adhesive of Excellent Peel strength, anti-corrosive & moisture resistant.

TECHNICAL PROPERTIS



Properties	Test Method	Unit	Specification
Color	Lab Test	n/a	Black
Total Thickness	ASTM D 3652	Micron	130 + 10
Peel Strength	ASTM D 3330	N/25mm	≥ 2
Tensile Strength	ASTM D 3759	N/25mm	≥ 20
Roll Ball Tack	ASTM D 3121	mm	≥ 100
Holding Power	ASTM D 3654	Hour	n/a
Temp. Resistance (30 min)	Lab Test	°C	70°C max

Note:

* Information on this data sheet is subject to change without prior notice and should not be used for writing specifications.

* For additional information on specific applications, contact Al Muqarram Insulation Industry L.L.C.

TYPICAL USES

- Air condition duct wrapping.
- Pipeline Protection.
- Moisture Proofing.

COLORS	AMI PVC Pipe Wrapping Tape is available in Black Color only
SLIT ROLLS	Width and length are available on request.
SERVICE TEMP.	70°C
APPLICATION TEMP.	10°C TO 55°C
PACKING	AMI PVC Pipe Wrapping Tape is available in 60 rolls per carton
STORAGE CONDITION	Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before six (6) months when stored at 25°C with 50% Relative Humidity
SHIPPING LIMITATIONS	None

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice