



Industrial Adhesives



**WORLD-CLASS
CHEMICALS**



Dolphin Contact Adhesive



PACKAGING

Sr. No.	Volume	Packaging type
1.	250 ml	Inner coated tin can
2.	650 ml	Inner coated tin can
3.	500 gms	Inner coated tin can
4.	3 Ltr	Inner coated tin can
5.	1 Gallon	Inner coated tin can

Dolphin Contact Adhesive forms an instant bond on contact and has a faster drying formula. It is ideal for bonding wood, MDF, laminate, PVC, leather, rubber and stone.

APPLICATIONS AREA

- Chemical resistance
- Bonds multiple substrates
- Quick drying formula
- High strength



Dolphin HVAC Contact Adhesive

Dolphin HVAC Contact Adhesive forms an instant bond on contact and has a faster drying formula. It is a multipurpose adhesive that bonds instantly on contact. It bonds many varieties of HVAC materials and will even fix non-porous surfaces together. For example wide range of DIY tasks repairs.

APPLICATIONS AREA

- PIR
- Phenolic duct



PACKAGING

Sr. No.	Volume	Packaging type
1.	3 kg	Inner coated tin can
2.	5 kg	Inner coated tin can
3.	13 Kg	Inner coated tin can





Dolphin CPVC Adhesive For hot water pipes

Dolphin CPVC medium bodied orange cement for bonding all schedules and classes of CPVC pipes and fittings up to 6" diameter with an interference fit. For residential and commercial hot and cold water systems up to 200°F / 93°C. Recommended application temperature 40°F to 110°F / 4°C to 43°C.

APPLICATIONS AREA

- One-part application
- Brush in can
- Rapid curing
- Strong and durable bonding
- Safe to use for bonding drinking water flowing pipes
- Meets BS & ASTM standards
- Easy to use



PACKAGING

Sr. No.	Volume	Packaging type
1.	118 ml	Inner coated tin can
2.	237 ml	Inner coated tin can
3.	476 ml	Inner coated tin can
4.	946 ml	Inner coated tin can



Dolphin UPVC Adhesive For normal water pipes

Dolphin UPVC medium bodied clear cement for bonding all schedules and classes of UPVC pipes and fittings up to 4" diameter with an interference fit. Recommended for potable water, pressure pipes and conduit DWV. Recommended application temperature 40°F to 110°F / 4°C to 43°C.

APPLICATIONS AREA

- One-part application
- Brush in can
- Rapid curing
- Strong and durable bonding
- Meets BS & ASTM standards
- Easy to use



PACKAGING

Sr. No.	Volume	Packaging type
1.	118 ml	Inner coated tin can
2.	237 ml	Inner coated tin can
3.	476 ml	Inner coated tin can
4.	946 ml	Inner coated tin can



Dolphin Floor Adhesive

Dolphin Floor Adhesive is based on premium quality synthetic resin, additives, tackifier and fine grade mineral fillers. It is acrylic water-based adhesive and compatible with most of the substrates.

APPLICATIONS AREA

- Multi purpose flooring & PVC vinyl adhesion
- Bonding of PVC sheet, vinyl coverings, tiles, EPDM sheet, polystyrene board, PU foam and similar materials like concrete, metals and wooden substrates
- Bonding substrates with porous & non-porous surfaces
- Floor heating installations (The heating should be switched off at least 48 hours before and after the installation of floor coverings)



PACKAGING

Sr. No.	Volume	Packaging type
1.	5 kg	Bucket
2.	10 kg	Bucket
3.	25 kg	Bucket
4.	200 Ltr	Drum



Dolphin
Industrial Grade Adhesives
“ The strongest and most durable bonding ”



Dolphin Nail Free Adhesive

Dolphin Nail Free Adhesive is ideal for fixing and mounting objects on the wall. Reliable, DIY (Do It Yourself) and just the right fit for interior general purpose applications.

APPLICATIONS AREA

- Instant tack (10 Sec)
- Water resistant
- Solvent rubber base
- Cures quickly



PACKAGING

Sr. No.	Volume	Packaging type
1.	465 Grm	Cartridge

TYPICAL USES OF DOLPHIN NAIL FREE ADHESIVE

General purpose construction adhesive

Bonding applications where high strength is required

Contact adhesive for installation of wall and floor panels

Adhesion of metal, timber & sheets of plane materials to concrete, plaster or other rigid surfaces

Timber, metal, cementitious and plaster sheets to timber or metal studs

Installation to brick, masonry or concrete walls



WORLD-CLASS CHEMICALS



Industrial Grade Adhesives

- | | | | |
|-----------------------|---------------|----------------|--------------------|
| Contact Adhesive | CPVC Adhesive | PIR Adhesive | Nail Free Adhesive |
| HVAC Contact Adhesive | UPVC Adhesive | Floor Adhesive | MDF BOND Activator |



AN ISO 9001:2015 (QMS), ISO 14001:2015 (EMS) & ISO 45001:2018 (OHSMS) CERTIFIED COMPANY



المكرم لصناعة المواد العازلة ذ.م.م
Al Muqarram Insulation Material Industry L.L.C

www.muqarram.com

@dolphinproducts [in](#) [ig](#) [fb](#) [tw](#) [yt](#)