

TECHNICAL DATA SHEET

AMI PVC PIPE WRAPPING TAPE

Revision Date: 14th June 2022

Revision No: 02

Number of Pages: 1

PRODUCT DESCRIPTION

AMI PVC Pipe Wrapping Tape is Polyvinylchloride film coated with Synthetic Rubber pressure-sensitive adhesive of Excellent Peel strength, anti-corrosive & moisture resistant.

TECHNICAL PROPERTIES



| Properties | Test Method | Specifications |
|---------------------------|-------------|-----------------|
| Color | Lab Test | Black |
| Total Thickness | ASTM D 3652 | 130 ± 10 micron |
| Peel Strength | ASTM D 3330 | ≥ 2 N/25mm |
| Tensile Strength | ASTM D 3759 | ≥ 20 N/25mm |
| Roll Ball Tack | ASTM D 3121 | ≤ 100 |
| Holding Power | ASTM D 3654 | n/a |
| Temp. Resistance (30 min) | Lab Test | 70°C max |

(Information on this data sheet is subject to change without prior notice and should not be used for writing specifications)

(For additional information on specific applications, contact Al Muqarram Insulation Industry L.L.C.)

TYPICAL USES

- Electrical wire Harnessing
- Electrical Insulation

| | |
|----------------------|---|
| Colors | AMI PVC Pipe Wrapping Tape is available in Black Color only |
| Slit rolls | Width and length are available on request. |
| Service temp. | 70°C |
| Application temp. | 10°C TO 55°C |
| Packing | AMI PVC Pipe Wrapping Tape is available in 60 rolls per carton |
| Storage condition | Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before six (6) months when stored at 25°C with 50% Relative Humidity |
| Shipping limitations | None |

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.