

الــــمكــــرم لــــصـــناعة المــــواد الــــعازلة ذ.م.م Al Mugarram Insulation Material Industry L.L.C.

MATERIAL SAFETY DATA SHEET

	DOLPHIN 30-36 AF	
Revision Date: 9 th Mar, 2021	Revision No. 2	Number of Pages: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Details

Product Name : DOLPHIN 30-36 AF
Product Code : AMI 30-36 AF

Recommended Use : Antifungal HVAC Canvas Coating

Company Details

Company Name : Al Muqarram Insulation Materials Industry L.L.C.

Address : Industrial Area # 15, Post Box No. 24756

Sharjah, United Arab Emirates

Phone Number : +971 (6) 5353796 Fax No. : +971 (6) 5353964

E-mail ID : info@muqarram.com, sales@muqarram.com

Website : www.muqarram.com

Emergency Telephone Number: 00971-549981925

2. HAZARDS IDENTIFICATION

Information pertaining to particular dangers for man

and environment

: Safe water based product.

: Avoid contact with skin or eyes. : Harmful if inhaled or swallowed.

: Inhalation of vapor or mist should be avoided. Symptoms include coughing, wheezing, laryngitis, and

shortness of breath, headache, nausea, and vomiting. : This material is non-corrosive to all body tissues.

: Ingestion causes nausea, vomiting, and loss of consciousness.

3. COMPOSITION/INFORMATION ON INGREDIENTS		
CAS No.	%W	CHEMICAL NAME
7732-18-5	10 – 40	Water
471-34-1	15 – 50	Calcium Carbonate
14808-60-7	05 – 15	Crystalline Silica
13463-67-7	02 – 10	Titanium Dioxide

4. FIRST AID MEASURES	5
Inhalation	: Move victim to fresh air and if needed, immediately begin artificial respiration. Give oxygen if
	breathing is labored. Get emergency medical help. Contact a physician immediately.
Skin Contact	: Flush with water or soap and water for 15 minutes or until all traces have been removed. Seek
	medical attention if symptoms develop and persist.
Eye Contact	: Flush eyes with water for 15 minutes. Get medical attention
Ingestion	: Do not induce vomiting. Rinse mouth out with water. Get immediate medical attention.
Note to Physician	: Treatment is symptomatic.

5. FIRE FIGHTING MEASURES

AMI | MSDS | info@muqarram.com | www.muqarram.com Page



ــمكـــــرم لـــــصــــناعة المـــــواد الـــــعازلة ذ.م.م Al Mugarram Insulation Material Industry L.L.C.

Media suitable for

: Use Dry powder, Carbon Dioxide (CO2), water fog or spray

Extinguishing

Special exposure hazards arising from the substance or preparation itself, its

combustion product, or

: In the event of fire the following can be released: Smoke, irritating vapor, Carbon

Monoxide (CO) and Carbon Dioxide (CO2).

released gases

Special protective

: Wear self-contained breathing apparatus and protective suit.

equipment for firefighters **Further information**

Handling

: In the event of fire, Approach fire from upwind side. Avoid breathing smoke, fumes, mist, or vapors on

the downwind side.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions : Ensure adequate ventilation. If TLV is exceeded wear NIOSH approved respirator.

Use heavy rubber type gloves, full-face shield and boots, aprons. Drench showers and Eye wash as

needed for protection against spills and/or splashes.

: Do not discharge into drains / surface water / groundwater. **Environment precautions**

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, sawdust). Collect spilled materials in suitable

containers and dispose of according to Section 13

7. HANDLING AND STORAGE

Precautions for Safe : Avoid contact with skin, eyes and clothing. After handling this product, wash hands before eating,

drinking or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action

shown in section 4. Launder contaminated clothing before reuse.

Proper Storage Condition : Store in a cool, dry, ventilated location. Keep away from heat, sparks, flame and other sources of

ignition. Keep container closed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure : Avoid contact with skin and eyes. Do not breathe vapors. Avoid repeated exposure. Wear suitable controls

protective equipment. Hold eye wash fountain available. Hold emergency shower available. Remove

soiled or soaked clothing immediately. Clean skin thoroughly after work.

At work do not eat, drink, smoke or take drugs. Keep away from food, drink and animal feeding stuffs.

Keep and wash working clothes separately.

Engineering Controls : Proper ventilation is recommended for controlling exposures.

Local exhaust is preferred.

Respiratory Protection : Use appropriate respirator unless local exhaust ventilation is sufficient.

Hand Protection : Rubber type gloves.

Eye Protection : If risk of splashing, wear safety goggles with side shields.

Other Protective Equipment : Wear suitable protective clothing such as aprons against splashing and contamination.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form : Paste Color : White

Properties

Odor : Mild Specific Gravity @ 25°C : 1.38 - 1.46

Viscosity : 30000 - 50000 cPs (Spindle 6, rpm-20, 25°C)

Solid (%) : 60 - 64**Boiling Point (°C)** : Not established **Melting Point** : Not established **Evaporation Rate** : Not established **Flash Point** : Not established **Auto Ignition Temperature** : Not established

AMI MSDS info@muqarram.com www.muqarram.com **Page**



الــــمكــــرم لـــصـــناعة المــــواد الــــعازلة ذ.م.م Al Muqarram Insulation Material Industry L.L.C.

Vapor Pressure: Not establishedVapor Density: Not established

10. STABILITY AND REACTIVITY

Stability : Stable under normal temperature conditions.

Material to avoid : High Temperatures

Hazardous decomposition : Upon combustion, Smoke, Irritating vapor, Carbon Monoxide and Carbon

products Dioxide are formed

11. TOXICOLOGICAL INFORMATION

CHEMICAL NAME :LD50/LC50

Calcium Carbonate, (rat) : Acute oral toxicity (LD50): 6450 mg/kg

12. ECOLOGICAL INFORMATION

Eco-toxicity: No data available.Mobility: No data available.Persistence / Degradability: No data available.Bio-accumulative potential: No data available.Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Product (Recommendation) : The product is not classified as a hazardous waste. The product can be coagulated and separated from

the aqueous phase for landfill or incineration.

Used packaging: Wash empty packaging. They can be reuse after thorough and proper cleaning.

(Recommendation)

Cleaning agent : Water

(Recommendation)

14. TRANSPORT INFORMATION

Proper Shipping Name : Adhesive, Non corrosive liquid, alkaline, inorganic

DOT Emergency Guide No : 154

15. REGULATORY INFORMATION

Risk Phrases : Not Classified

Safety Phrases : Wear suitable protective clothing, gloves and eye/face protection.

Chemical Safety Assessment: A chemical safety assessment has not been carried out.

16. OTHER INFORMATION

General Information : This product should be used as directed. For further information, please consult product data sheets

and application information bulletin for this product.

Further Information: The information contained herein is based on the present state of our knowledge. It characterizes the

product with regard to the appropriate health and safety precaution, and hazard information. It does not

represent a guarantee of the properties of product.

Revision Comments : This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is correct.

AMI | MSDS | info@muqarram.com | www.muqarram.com Page