

MATERIAL SAFETY DATA SHEET

DOLPHIN Contact Adhesive

Revision No. 2 Revision Date: 9th Mar, 2021 Number of Pages: 4

1. PRODUCT AND COMPANY IDENTIFICATION

Product Details

Product Name : DOLPHIN Contact Adhesive **Product Code** : AMI Contact Adhesive **Recommended Use** : Adhesive / Glue

Company Details

Company Name : Al Mugarram Insulation Materials Industry L.L.C.

Address : Industrial Area # 15, Post Box No. 24756

Sharjah, United Arab Emirates

Phone Number : +971 (6) 5353796 Fax No. : +971 (6) 5353964

E-mail ID : info@mugarram.com, sales@mugarram.com

Website : www.mugarram.com

Emergency Telephone Number: 00971-549981925

2. HAZARDS IDENTIFICATION

: Extremely Flammable

: Can cause eye irritation.

Information pertaining to

: Can cause skin irritation.

particular dangers for man

: Moderate Respiratory tract irritant.

and environment

: Harmful if swallowed.

: Inhalation of vapors may cause loss of feeling and weakness in the hands and feet and loss of manual dexterity. Inhalation of high concentrations may results in central nervous system effects such as dizziness, weakness, fatigue, nausea, headache, and lack of

coordination.

3. COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description:

Moisture-curing neutral cilicone spalant

Moisture-curing fleutral shicone sealant		
CAS No.	%W	CHEMICAL NAME
8050-31-5	20 – 30	Ester Resin
110-54-3	40 – 60	Hexane
9006-04-06	10 – 15	Thermoplastic Rubber
141-78-6	10 - 15	Ethyl Acetate



الـــــمكـــــرم لـــــصــــناعة المـــــواد الـــــعازلة ذ.م.م Al Mugarram Insulation Material Industry L.L.C.

4. FIRST AID MEASURES

Inhalation : Move to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

Skin Contact : Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if

irritation develops or persists.

: Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the **Eye Contact**

head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical

attention and monitor the eye daily as advised by your physician.

Ingestion : Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk

to dilute. Do not give anything by mouth to an unconscious person. Induce vomiting as a last

measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing

chemical pneumonitis that may be fatal.

Note to Physician : Treatment is symptomatic.

5. FIRE FIGHTING MEASURES

Media suitable for

Extinguishing

Special exposure hazards

arising from the substance or preparation itself, its

combustion product, or

released gases

: Use water spray, foam, dry chemical or carbon dioxide.

Smoke, irritating vapor, Carbon

Monoxide (CO) and Carbon Dioxide (CO2)

: In the event of fire the following can be released:

Special protective

equipment for firefighters

: Wear self-contained breathing apparatus and protective suit.

Further information : In the event of fire, vapor are heavier than air and can travel to ignition source and flash back.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions : Wear personal protective equipment; Ensure adequate ventilation. **Environment precautions** : Do not discharge into drains / surface water / groundwater.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, sawdust).

Collect spilled materials in suitable containers and dispose of according to Section 13

7. HANDLING AND STORAGE

Precautions for Safe

Handling

: Mildly irritating material. Avoid unnecessary exposure. Keep away from heat, sparks and flame. Wash thoroughly after handling. Keep container closed. Emptied container retains vapor and product residue. Observe precautions until container is cleaned. Drum of this material should be grounded when pouring.

Do not cut or weld on or near this container.

Avoid contact with skin and eyes.

Proper Storage Condition : Store in a cool, dry, ventilated location. Keep away from heat, sparks, flame and other sources of

ignition. Keep container closed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure

controls

: Avoid contact with skin and eyes. Do not breathe vapors. Avoid repeated exposure. Wear suitable protective equipment. Hold eye wash fountain available. Hold emergency shower available. Remove

soiled or soaked clothing immediately. Clean skin thoroughly after work. : Proper ventilation is recommended for controlling exposures. Local exhaust is preferred.

Engineering Controls Respiratory Protection : Use appropriate respirator unless local exhaust ventilation is sufficient.

Hand Protection : Latex gloves.

Eye Protection : If risk of splashing, wear safety goggles with side shields.

Other Protective Equipment : Wear suitable protective clothing such as aprons against splashing and Contamination

MSDS AMI www.mugarram.com



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form : Medium-viscosity, flowable liquid

Color : Clear-Pale Yellow

Properties

Odor : Solvent odor Specific Gravity @ 25°C : 0.85 ± 0.05

Viscosity : 2000 ± 500 cPs (@ 25°C)

Solid (%) : 40 + 5

Boiling Point (°C): Not determinedMelting Point: Not determinedEvaporation Rate: Not established

Flash Point : <10°C

Auto Ignition Temperature : Not established

Vapor Pressure : Not established Vapor Density : Not established

10. STABILITY AND REACTIVITY

Stability : Stable under normal temperature conditions.

Material to avoid : Keep away from heat sources

Hazardous decomposition

products

: Upon combustion Carbon Monoxide and Carbon Dioxide are formed

11. TOXICOLOGICAL INFORMATION

Chemical name : LD₅₀/LC₅₀

Hexane, (rat) : Acute oral toxicity (LD50) : 25000 mg/kg

Acute toxicity of the gas (LC50): 48000 mg/kg (4hr)

Ester Resin, (rat) : LD₅₀- >2000 mg/kg

LC₅₀- 2500 mg/kg (90d)

12. ECOLOGICAL INFORMATION

Eco-toxicity: No data availableMobility: No data availablePersistence / Degradability: No data availableBio-accumulative potential: No data availableOther adverse effects: No data available

13. DISPOSAL CONSIDERATIONS

Product : This product meets the definition of hazardous waste. It is ignitable waste class

(Recommendation) D001. Disposal via incineration is recommended.

Used packaging : Wash empty packaging.

(Recommendation)

Cleaning agent : Solvent

MSDS

(Recommendation)

AMI

info@mugarram.com www.mugarram.com



الــــمكــــرم لــــصـــناعة المــــواد الــــعازلة ذ.م.م Al Muqarram Insulation Material Industry L.L.C.

14. TRANSPORT INFORMATION

Dangerous Goods Class : 3

Proper Shipping Name : Adhesive, containing flammable liquid

 Packing Group
 : III

 Hazchem Code
 : 3 [Y]

 EPG No.
 : 3C1

 UN No
 : 1133

15. REGULATORY INFORMATION

Risk Phrases : Not Classified

Safety Phrases: Wear suitable protective clothing, gloves and eye/face protection.

Chemical Safety Assessment: A chemical safety assessment has not been carried out.

16. OTHER INFORMATION

General Information : This product should be used as directed. For further information, please consult product data sheets

and application information bulletin for this product.

Further Information : The information contained herein is based on the present state of our knowledge. It characterizes the

product with regard to the appropriate health and safety precaution, and hazard information.

It does not represent a guarantee of the properties of product.

Revision Comments : This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is correct.