



TECHNICAL DATA SHEET

DOLPHIN DIESEL FUEL TREATMENT		
Revision Date: 11 th April 2021	Revision No: 2	Number of Pages: 2

PRODUCT DESCRIPTION

Dolphin Diesel Fuel Treatment is especially formulated to provide vehicle engine a peak performance in all seasons. Cleans, lubricates and protects all vital components of the engine including pumps, cylinder walls and injector walls and eliminates high temperature deposits.

TECHNICAL PROPERTIES

	Properties	Specifications
	Appearance	Clear Orange
and the second se	Physical State	Liquid
Dolphin	Specific Gravity	0.790 – 0.820
T	Flash Point	40°C
Dolphin		

(Information on this data sheet is subject to change without prior notice and should not be used for writing specifications)

KEY FEATURES

- Increases vehicle engine performance and fuel economy
- Improves air quality as it decreases polluted diesel fuel, exhaust fumes
- Prevents engine surface from rusting and decrease harmful diesel fuel fumes
- Cleans the entire diesel fuel system
- Improves the combustion and facilitates cold starting
- Reduces diesel knocking noises
- Reduces black exhaust smoke

TDS

- Cleans and lubricates injectors and fuel pump
- Protects the entire fuel system against rust and corrosion
- Harmless for all after-treatment systems

AMI |

info@muqarram.com

www.muqarram.com

Head Office

♥ P.O. Box 24756, Sharjah, U.A.E. **↓** +971 6 535 3796

😆 info@mugarram.com 🔀 www.mugarram.com









الـــــمكــــرم لــــصـــناعة المــــواد الــــعازلة ذ.م.م منتقد المــــواد الــــعازلة د.م.م Al Muqarram Insulation Material Industry L.L.C.

Directions for use	 Application surface should be dry and dust, rust, and grease-free For best result apply it within defined temperature (From 25°C to 45°C) Recommended for all diesel engines In case of diesel knocking, difficult starting, too much black exhaust smoke, poor functioning of pump and injectors, high fuel consumption 	
Packaging	Dolphin Diesel Fuel Treatment is available in 354 ML bottle.	
Storage and shelf life	Store in a dry and well-ventilated storeroom at the temperature below 40 °C. Dolphin Diesel Fuel Treatment has a shelf life of 36 months from date of manufacturing.	
Handling precautions	Avoid contact with eyes and skin. In case of eye contact, immediately flush with plenty of water and take medical advice.	
KEEP OUT OF REACH OF CHILDREN • KEEP CONTAINER TIGHTLY CLOSED • FOR INDUSTRIAL & POFESSIONAL USE		

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

AMI

TDS

info@muqarram.com

