



MATERIAL SAFETY DATA SHEET

DOLPHIN CONTACT ADHESIVE GP

Revision Date: 5th July 2024 Revision No. 00 Number of Pages: 04

1. PRODUCT AND COMPANY IDENTIFICATION

Product Details

Product Name : DOLPHIN CONTACT ADHESIVE GP
Product Code : AMI Contact Adhesive GP

Recommended Use : Adhesive

Company Details

Company Name : Al Mugarram Insulation Materials Industry L.L.C.

Address : Industrial Area # 15, Post Box No. 24756, Sharjah, United Arab Emirates

 Phone Number
 : +971 (6) 5353796

 Fax No.
 : +971 (6) 5353964

 E-mail ID
 : info@muqarram.com

 Website
 : www.muqarram.com

Emergency Telephone Number: 00971-549981925

2. HAZARDS IDENTIFICATION

Information pertaining to dangers for man and environment:

Extremely Flammable

Can cause eye irritation.

Can cause skin irritation.

Moderate Respiratory tract irritant.

Harmful if swallowed.

Inhalation of vapors may cause loss of feeling and weakness in the hands and feet and loss of manual dexterity. Inhalation of high concentrations may result in central nervous system effects such as dizziness, weakness, fatigue, nausea, headache, and lack of coordination.

3. COMPOSITION/INFORMATION ON INGREDIENT

Mixture

Head Office

General Chemical Description:

Solvent based rubber adhesive.

CAS No.	%W	CHEMICAL NAME
8050-31-5	20 – 25	Ester Resin
110-54-3	40 – 60	Hexane
9006-04-06	15 – 20	Thermoplastic Rubber
67 – 64 -1	20 - 30	Acetone

AMI | MSDS | info@muqarram.com | www.muqarram.com Page 1 of 4





4. FIRST AID MEASURES

Inhalation : Move to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

: Wash with soap and water. Remove contaminated clothing and launder. Get medical **Skin Contact**

attention if irritation develops or persists.

Eve Contact : Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids

often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your

physician.

Ingestion : Do not induce vomiting and seek medical attention immediately. Drink two glasses of

> water or milk to dilute. Do not give anything by mouth to an unconscious person. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

Note to Physician : Treatment is symptomatic.

FIRE FIGHTING MEASURES

Media suitable for Extinguishing

Special exposure hazards arising from the substance or preparation itself, its combustion product, or released gases

Special protective equipment

for firefighters

Further information

: Use water spray, foam, dry chemical, or carbon dioxide.

: In the event of fire, the following can be released:

Smoke, irritating vapor, Carbon Monoxide (CO) and Carbon Dioxide (CO2)

: Wear self-contained breathing apparatus and protective suit.

: In the event of fire, vapor is heavier than air and can travel to ignition source and flash

back.

ACCIDENTAL RELEASE MEASURES

Personal Precautions : Wear personal protective equipment; Ensure adequate ventilation.

Environment precautions : Do not discharge into drains / surface water / groundwater.

: Soak up with inert absorbent material (e.g. sand, sawdust). Collect spilled materials in Methods for cleaning up

suitable containers and dispose of according to Section 13.

HANDLING AND STORAGE

Precautions for Safe Handling : Mildly irritating material. Avoid unnecessary exposure. Keep away from heat, sparks,

> and flame. Wash thoroughly after handling. Keep container closed. Emptied container retains vapor and product residue. Observe precautions until container is cleaned. Drum of this material should be grounded when pouring. Do not cut or weld on or near

this container. Avoid contact with skin and eyes.

: Store in a cool, dry, ventilated location. Keep away from heat, sparks, flame, and other **Proper Storage Condition**

sources of ignition. Keep container closed.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure controls : Avoid contact with skin and eyes. Do not breathe vapors. Avoid repeated exposure. Wear

suitable protective equipment. Hold eye wash fountain available. Hold emergency shower available. Remove soiled or soaked clothing immediately. Clean skin thoroughly after

Engineering Controls : Proper ventilation is recommended for controlling exposures. Local exhaust is preferred.

Respiratory Protection : Use appropriate respirator unless local exhaust ventilation is sufficient.

Hand Protection : Latex gloves.

Eye Protection : If risk of splashing, wear safety goggles with side shields.

MSDS www.muqarram.com Page 2 of 4 AMI info@muqarram.com









Other Protective Equipment : Wear suitable protective clothing such as aprons against splashing and Contamination.

: Avoid

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form : Free flowing adhesive
Color : Yellow to Brown

Properties

 Odor
 : Solvent odor

 Specific Gravity @ 25°C
 : 1.04 ± 0.05

Viscosity : 1400 - 1800 cPs (@ 25°C)

Solid (%) : 45 - 50

Boiling Point (°C): Not determinedMelting Point: Not determinedEvaporation Rate: Not establishedFlash Point: <20°C</th>

Auto Ignition Temperature: Not establishedVapor Pressure: Not establishedVapor Density: Not established

10. STABILITY AND REACTIVITY

Stability : Stable under normal temperature conditions.

Material to avoid : Keep away from heat sources

Hazardous decomposition products : Upon combustion Carbon Monoxide and Carbon Dioxide are formed

11. TOXICOLOGICAL INFORMATION

Chemical name : LD₅₀/LC₅₀

Hexane, (rat) : Acute oral toxicity (LD50): 25000 mg/kg

Acute toxicity of the gas (LC50): 48000 mg/kg (4hr)

Ester Resin, (rat) : LD₅₀- >2000 mg/kg

LC₅₀- 2500 mg/kg (90d)

12. ECOLOGICAL INFORMATION

Eco-toxicity: No data availableMobility: No data availablePersistence / Degradability: No data availableBio-accumulative potential: No data availableOther adverse effects: No data available

13. DISPOSAL CONSIDERATIONS

Product (Recommendation) : This product meets the definition of hazardous waste. It is ignitable waste class

D001. Disposal via incineration is recommended.

Used packaging (Recommendation) : Wash empty packaging.

Cleaning agent (Recommendation) : Solvent

AMI | MSDS | info@muqarram.com | www.muqarram.com Page 3 of 4







14. TRANSPORT INFORMATION

Dangerous Goods Class : 3

Proper Shipping Name : Adhesive, containing flammable liquid

 Packing Group
 : III

 Hazchem Code
 : 3 [Y]

 EPG No.
 : 3C1

 UN No
 : 1133

15. REGULATORY INFORMATION

Risk Phrases : Not Classified

Safety Phrases : Wear suitable protective clothing, gloves, and eye/face protection.

Chemical Safety Assessment : A chemical safety assessment has not been carried out.

16. OTHER INFORMATION

General Information

This product should be used as directed. For further information, please consult product data sheets and application information bulletin for this product.

Further Information

The information contained herein is based on the present state of our knowledge. It characterizes the product regarding the appropriate health and safety precaution, and hazard information. It does not represent a guarantee of the properties of product.

Revision Comments

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is correct.



AMI | MSDS | info@muqarram.com | www.muqarram.com Page 4 of 4