

TECHNICAL DATA SHEET

AMI HT 80 MASKING TAPE

Revision Date: 14th June 2022

Revision No: 02

Number of Pages: 1

PRODUCT DESCRIPTION

AMI 80 Masking Tape is a saturated crepe paper coated with a rubber adhesive: high shear strength, and excellent adhesion. It easy to tear without leaving a residue or damaging the surface to which it is applied.

TECHNICAL PROPERTIES



Properties	Test Method	Specifications
Color	Lab Test	Visually Yellow
Backing	Lab test	Crepe Paper
Adhesive	Lab test	Rubber Based
Total Thickness	ASTM D 3652	135 ± 15 micron
Peel Strength	ASTM D 3330	≥ 4 N/25mm
Tensile Strength	ASTM D 3759	≥ 50 N/25mm
Rolling Ball Tack	ASTM D 3121	≤ 100 mm
Holding Power	ASTM D 3654	≥ 10 Hours

(Information on this data sheet is subject to change without prior notice and should not be used for writing specifications)
(For additional information on specific applications, contact Al Muqarram Insulation Industry L.L.C.)

TYPICAL USES

- General-purpose packing
- Bundling, Labelling, Paint masking
- For paint masking at medium temperature

Colors	AMI 80 Masking Tape is available in natural color only.
Slit rolls & jumbo rolls	Width and length are available on request.
Service temp.	Max. 80°C
Application temp.	25°C TO 35°C
Packing	AMI 80 Masking Tape is available in 16, 24 and 36 standard rolls per carton. 1250 mm width x 1800 meters length jumbo roll.
Storage condition	Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before twelve (12) months when stored at 25°C with 50% Relative Humidity.
Shipping limitations	None

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.