

# TECHNICAL DATA SHEET

## AMI PVC PIPE WRAPPING TAPE

Revision Date: 14<sup>th</sup> June 2022

Revision No: 02

Number of Pages: 1

## PRODUCT DESCRIPTION

AMI PVC Pipe Wrapping Tape is Polyvinylchloride film coated with Synthetic Rubber pressure-sensitive adhesive of Excellent Peel strength, anti-corrosive & moisture resistant.

## TECHNICAL PROPERTIES



Properties	Test Method	Specifications
Color	Lab Test	Black
Total Thickness	ASTM D 3652	130 ± 10 micron
Peel Strength	ASTM D 3330	≥ 2 N/25mm
Tensile Strength	ASTM D 3759	≥ 20 N/25mm
Roll Ball Tack	ASTM D 3121	≤ 100
Holding Power	ASTM D 3654	n/a
Temp. Resistance (30 min)	Lab Test	70°C max

(Information on this data sheet is subject to change without prior notice and should not be used for writing specifications)  
(For additional information on specific applications, contact Al Muqarram Insulation Industry L.L.C.)

## TYPICAL USES

- Electrical wire Harnessing
- Electrical Insulation

Colors	AMI PVC Pipe Wrapping Tape is available in Black Color only
Slit rolls	Width and length are available on request.
Service temp.	70°C
Application temp.	10°C TO 55°C
Packing	AMI PVC Pipe Wrapping Tape is available in 60 rolls per carton
Storage condition	Tapes should be stored in a cool, dry area away from direct sunlight and other heat sources. Tapes can be used before six (6) months when stored at 25°C with 50% Relative Humidity
Shipping limitations	None

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.