

AN ISO CERTIFIED COMPANY

PRODUCT

منعفى الإمارات MADE IN UAE

الـــــمكــــرم لــــصـــناعة المــــواد الــــعازلة ذ.م.م Al Muqarram Insulation Material Industry L.L.C.

MATERIAL SAFETY DATA SHEET

DOLPHIN AM-40 ANTI RUST LUBRICANT

Revision Date: 9 th March 2021	Revision No. 02	Number of Pages: 07
1. PRODUCT AND COMPA	NY IDENTIFICATION	
Product Details		
Product Name	: DOLPHIN AM-40 ANTI RUST LU	BRICANT SEROSOL SPRAY
Recommended Use	: Anti Rust Lubricant	
<u>Company Details</u>		
Company Name	: Al Muqarram Insulation Mater	ials Industry L.L.C.
Address	: Industrial Area # 15, Post Box N	No. 24756, Sharjah, United Arab Emirates
Phone Number	: +971 (6) 5353796	
Fax No.	: +971 (6) 5353964	
E-mail ID	: info@muqarram.com	
Website	: www.muqarram.com	

Emergency Telephone Number: 00971-549981925

2. HAZARDS IDENTIFICATION

Physical Hazards Flammable aerosol	: Category 1
Gases under pressure	: Compressed gas
Cases under pressure	. compressed gas
Health Hazards	
Aspiration Toxicity	: Category 1
Eye Irritant	: Category 2A
Skin Irritant	: Category 2
Environmental Hazards	
Aquatic Acute Toxicity	: Category 3
Aquatic Chronic Toxicity	: Category 3
Lebel Elements	
	Contains: Naphtha (petroleum), hydro desulfurized heavy (Petroleum Base Oil) and Additives
Danger	
Danger H222	
	Additives
H222	Additives : Extremely flammable aerosol.
H222 H280	Additives : Extremely flammable aerosol. : Contains gas under pressure: may explode if heated.
H222 H280 H304	Additives : Extremely flammable aerosol. : Contains gas under pressure: may explode if heated. : May be fatal if swallowed and enters airways.
H222 H280 H304 H315	Additives : Extremely flammable aerosol. : Contains gas under pressure: may explode if heated. : May be fatal if swallowed and enters airways. : Causes skin irritation.
H222 H280 H304 H315 H319	Additives : Extremely flammable aerosol. : Contains gas under pressure: may explode if heated. : May be fatal if swallowed and enters airways. : Causes skin irritation. : Causes serious eye irritation.
H222 H280 H304 H315 H319 H412	Additives : Extremely flammable aerosol. : Contains gas under pressure: may explode if heated. : May be fatal if swallowed and enters airways. : Causes skin irritation. : Causes serious eye irritation.
H222 H280 H304 H315 H319 H412 Prevention	Additives : Extremely flammable aerosol. : Contains gas under pressure: may explode if heated. : May be fatal if swallowed and enters airways. : Causes skin irritation. : Causes serious eye irritation. : Harmful to aquatic life with long lasting effects.
H222 H280 H304 H315 H319 H412 Prevention P210	Additives : Extremely flammable aerosol. : Contains gas under pressure: may explode if heated. : May be fatal if swallowed and enters airways. : Causes skin irritation. : Causes serious eye irritation. : Harmful to aquatic life with long lasting effects. : Keep away from heat, sparks, open flames and hot surfacesNo smoking.

Head Office

የ P.O. Box 24756, Sharjah, U.A.E. 🌜 +971 6 535 3796 🐱 info@muqarram.com 🕲 www.muqarram.com





الـــــمكــــرم لــــصـــناعة المــــواد الــــعازلة ذ.م.م Al Muqarram Insulation Material Industry L.L.C.

P273	: Avoid release to the environment.
P280	: Wear protective gloves and eye protection.
Response	
P302+P352	: IF ON SKIN: Wash with plenty of soap and water.
P332+P313	: If skin irritation occurs: Get medical attention.
P362	: Take off contaminated clothing and wash it before reuse
P305+P351+P338	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	: If eye irritation persists: Get medical attention
P301+P310	: IF SWALLOWED: Immediately call a POISON CENTER or doctor or physician. Do NOT induce vomiting.
Storage	
P410+P412	: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P403+P235	: Store in a well-ventilated place. Keep cool.
P405	: Store locked up.
Disposal	
P501	: Dispose of contents and container in accordance with local and national regulations.
Other haards that do not Result in	n Classification

None

3. COMPOSITION/INFORMATION ON INGREDIENT

Chemical Identity	CAS # Wt. %		Substance Classification	
Naphtha (petroleum), hydro desulfurized heavy	64742-82-1	15 – 20	Flam. Liq. Cat 3 (H226) Asp. Tox. Cat 1 (H304)	
Additives	Proprietary	<1	Eye Damage. Cat 1 (H318) Skin Irritation. Cat 2 (H315)	

4. FIRST AID MEASURES	
Inhalation	: If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.
Skin Contact	: Wash with soap and water. If irritation develops and persists, get medical attention.
Eye Contact	: Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists.
Ingestion	: Aspiration Hazard. DO NOT induce vomiting. Call a Poisons Information Center immediately.
Indication of Immediate Medical Attention and Special Treatment, if Needed	: Immediate medical attention is required for ingestion.

5. FIRE FIGHTING MEASURES

Ext	inguisł	ning medi	а			e water fog, dry chemical, carbon dioxide or foam. Do not use water je nounts of water. Burning product will float on the surface and spread f	U
		izards aris	sing fr	om the substance or		remely flammable aerosol. Contents under pressure. Keep away from	0
mi	kture				SO	urce and open fire. Exposure of containers to extreme heat and flames	s can cause
AMI		MSDS		info@muqarram.com		www.muqarram.com	Page 2 of 7





منع في الإمارات MADE IN UAE



الــــــمكـــــرم لـــــصــــناعة المـــــواد الـــــعازلة ذ.م.م ففقت Al Muqarram Insulation Material Industry L.L.C.

them to rupture often with violent force. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion hazard in confined spaces : Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding

Advice for firefighters

amounts of water. Burning product will float on the surface and spread fire.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Environment precautions Methods And Material For **Containment And Cleaning Up**

- : Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area
- : Avoid releases to the environment. Report spills to authorities as required.
- : Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly.

7. HANDLING AND STORAGE

Precautions for Safe Handling	: Avoid contact with eyes and skin. Avoid breathing vapors or aerosols. Intentional misuse by deliberately concentrating vapors and inhaling can be harmful or fatal. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces, and open flames. Unplug electrical tools, motors, and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture,
	crush, or incinerate containers, even when empty.
Proper Storage Condition	: Store in a cool, dry ventilated area away from incompatible materials. Protect from physical damage. Do not store in direct sunlight, near open flames or above temperatures greater than 50°C.

EXPOSURE CONTROLS/PERSONAL PROTECTION 8.

Chemical Identity	Occupational Exposure Limits	Biological Limit Value
Naphtha (petroleum), hydro desulfurized heavy	350 mg/m3 TWA (manufacturer recommended) 5 mg/m3 TWA AU OEL (as oil mist, refined mineral) 5 mg/m3 TWA, 10 mg/m3 STEL NZ OEL (as oil mist, mineral) 5 mg/m3 TWA ACGIH TLV (inhalable) (as mineral oil)	None Established
Petroleum Base Oil	5 mg/m3 TWA AU OEL (as oil mist, refined mineral) 5 mg/m3 TWA, 10 mg/m3 STEL NZ OEL (as oil mist, mineral) 5 mg/m3 TWA ACGIH TLV (inhalable) (as mineral oil)	None Established
Additives	None Established	None Established
Engineering Controls: Use in a well-ventilated area.Eye/Face Protection: Avoid eye contact. Always spray product away from your face.Respiratory Protection: None needed for normal use with adequate ventilation.Skin Protection: Avoid prolonged or repeated skin contact. Chemical resistant gloves recommended for operations where skin contact is likely.		
II MSDS info@mu	garram.com www.mugarram.com	Page 3 of

Head Office

የ P.O. Box 24756, Sharjah, U.A.E. 🌜 +971 6 535 3796 🐱 info@muqarram.com 🕲 www.muqarram.com



الـــــمكــــرم لــــصــــناعة المــــواد الــــعازلة ذ.م.م Al Muqarram Insulation Material Industry L.L.C.

For Bulk Processing or Workplace Use the Following Controls are recommended.

Appropriate Engineering Controls	: Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.
Eye Protection	: Safety goggles recommended where eye contact is possible.
Skin Protection	: Wear chemical resistant gloves
Respiratory Protection	: None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear an approved respirator. Respirator selection and use should be based on contaminant type, form, and concentration. Follow applicable regulations and good Industrial Hygiene practice.
Work/Hygiene Practices	: Eye wash facilities should be available. Wash hands after handling.

Other Protective Equipment

: None required.

PHYSICAL AND CHEMICAL PROPERTIES 9.

Appearance	
Form	: Liquid
Color	: Aerosol
Properties	
Odor	: Pleasant odor
Odor Threshold	: Not determined
рН	: Not determined
Melting/Freezing Point	: Not applicable
Partition Coefficient of n-octanol/water	: Not determined
Auto-ignition temperature	: Not determined
Decomposition temperature	: Not determined
Viscosity	: Not determined
Boiling Point/Range	: 162-192°C (324-378°F) (Concentrate)
Flash Point	: 41-42°C (106-108°F) (Concentrate)
Evaporation Rate	: Not determined
(Butyl Acetate = 1)	
Flammability (solid, gas)	: LEL 0.7% UEL 7.0% (Concentrate)
Vapor Pressure	: 724 kPa @ 21°C (69.8°F)
Vapor Density (air =1)	:>1
Relative Density (Water = 1)	: Not determined
Specific Heat Value	: Not determined
Particle Size	: Not applicable
VOC	: 49.5%
Percent Volatile	: 78%
Saturated Vapor Concentration	: Not determined
Release of invisible flammable vapors and	: Yes
gases	
Aerosol Protection Level (NFPA 30B)	:3
Solubility	: Insoluble in water

10. STABILITY AND REACTIVITY

Reactivity	: Non-reactive.
Chemical stability	: Stable under normal storage conditions.
Possibility of hazardous Reactions	: Will not occur.
Conditions to avoid	: Avoid extreme heat, flames, and other sources of ignition. Avoid physical damage to aerosol can.
Incompatible materials	: Strong oxidizers.
Hazardous decomposition Products	: Carbon monoxide and carbon dioxide

MSDS info@muqarram.com AMI T

www.muqarram.com

AN ISO CERTIFIED COMPANY

Page 4 of 7

مىنعەنى الإمارات MADE IN UAE

የ P.O. Box 24756, Sharjah, U.A.E. 🌜 +971 6 535 3796 🐱 info@muqarram.com 🕲 www.muqarram.com

Head Office





الـــــــمكـــــرم لـــــصـــــناعة المـــــواد الـــــعازلة ذ.م.م مخممه

Al Muqarram Insulation Material Industry L.L.C.

11. TOXICOLOGICAL INFORMATION		
Possible Health Effect		
Acute Effects		
Ingestion	: Swallowing is an unlikely route of exposure for an aerosol product. Swallowing large amounts may produce gastrointestinal irritation, nausea, vomiting and diarrheal. This product is an aspiration hazard. If swallowed, can enter the lungs, and may cause chemical pneumonitis, severe lung damage and death.	
Eye Contact	: Liquid sprayed into eyes may cause irritation. May cause redness, stinging, swelling, and tearing.	
Skin Contact	: May produce mild irritation. Prolonged and/or repeated contact may cause defatting with possible dermatitis.	
Inhalation	: Mist or vapor can irritate the throat and lungs. High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness, and nausea. Intentional abuse may be harmful or fatal.	
Chronic Exposure	: None known.	
Medical Conditions Aggravated by Exposure	: Pre-existing eye, skin and respiratory conditions may be aggravated by exposure.	
Acute Toxicity Values	: Naphtha (petroleum), hydro desulfurized heavy:	
	Oral rat LD ₅₀ - >5000 mg/kg.	
	Skin rabbit LD ₅₀ - >3160 mg/kg.	
	Petroleum Base Oil:	
	Oral rat LD ₅₀ ->15 gm/kg	
Non-Hazardous Ingredients	: No toxicity data available.	

12. ECOLOGICAL INFORMATION

Eco-toxicity	 This product has been classified as harmful to the aquatic environment with long lasting effects based on the components. Releases to the environment should be avoided. Naphtha (petroleum), hydro desulfurized heavy: 96 hr. LC50 Fathead minnow – 8.2 mg/L; 96 hr. LC50 Crannog Crannog – 4.3 mg/L
Persistence and Degradability	: No data available.
Bioaccumulation	: No data available.
Mobility in soil	: No data available.

13. DISPOSAL CONSIDERATIONS

Safe Handling and Disposal Method

: Aerosol containers should not be punctured, compacted in home trash compactors, or incinerated.

Disposal of Contaminated Packaging Environmental Regulations

- : Empty containers may be disposed of through normal waste management options. : Dispose of all waste product, absorbents, and other materials in accordance with
- applicable Federal, state, and local regulations.

14. TRANSPORT INFORMATION

AMI	I	MSDS		info@muqarram.com	www.muqarram.com	
UN Number					: UN Number	
IATA Hazard Class					: 2.1	
IATA Shipping Name			ne		: Aerosols, Flammable	
Marine Pollutant					: No	
UN Number					: UN Number	
IMDG Hazard Class			5		: 2.1	
IMDG Shipping Name					: Aerosols	
Road	1 & Ra	ail Transp	ort			

Head Office

.

የ P.O. Box 24756, Sharjah, U.A.E. 🌜 +971 6 535 3796







منعفى الإمارات MADE IN UAE



الـــــمكــــرم لــــصـــناعة المــــواد الــــعازلة ذ.م.م Al Muqarram Insulation Material Industry L.L.C.

: Aerosols : 2.1 : UN1950 : 2YE

ADG Shipping Name
ADG Hazard Class
UN Number
Hazchem (Emergency Action)
Code
Special Precautions for User

: Dolphin AM-40 manufacturer does not test aerosol cans to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our aerosol products be transported by air.

New Zealand Inventory: All the ingredients comply with the HSNO regulations.

15. REGULATORY INFORMATION

16. OTHER INFORMATION

egory 4
egory 2
gory 1
gory 1
egory 2
egory 3
egory 2
3
nmable liquid and vapor
be fatal if swallowed and enters airways
mful in contact with skin
ses skin irritation
ses serious eye damage
ses serious eye irritation
mful if inhaled
v cause respiratory irritation
ic to aquatic life with long lasting effects
erican Conference of Industrial Hygienists
ralian Dangerous Goods
ralian Inventory of Chemical Substances
ralia
ctive Concentration
www.muqarram.com Page 6 of 7

Head Office

የ P.O. Box 24756, Sharjah, U.A.E. 🌜 +971 6 535 3796

🐱 info@muqarram.com 🙂 www.muqarram.com





الـــــمكــــرم لــــصـــناعة المــــواد الــــعازلة ذ.م.م Al Muqarram Insulation Material Industry L.L.C.

EU	: European Union
GHS	: Globally Harmonized System of Classification and Labelling of Chemicals
HSNO	: Hazardous Substances and New Organisms
IARC	: International Agency of Research on Cancer
ΙΑΤΑ	: International Air Transport Association
IMDG	: International Maritime Dangerous Goods
LC	: Lethal Concentration
LD	: Lethal Dosage
LEL	: Lower Explosive Limit
NTP	: National Toxicology Program
OEL	: Occupational Exposure Limits
US OSHA	: United States Occupational Safety and Health Administration
PEL	: Permissible Exposure Limit
SDS	: Safety Data Sheet
STEL	: Short Term Exposure Limit
TWA	: Time-Weighted Average
UEL	: Upper Explosive Limit
VOC	: Volatile Organic Compounds
WHS	: Work Health and Safety

General Information

This product should be used as directed. For further information, please consult product data sheets and application information bulletin for this product.

Further Information

The information contained herein is based on the present state of our knowledge. It characterizes the product regarding the appropriate health and safety precaution, and hazard information. It does not represent a guarantee of the properties of product.

Revision Comments

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is correct.

17. DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated.

However, no warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

info@muqarram.com

www.muqarram.com