



MATERIAL SAFETY DATA SHEET

DOLPHIN SILICONE DASHBOARD POLISH

Revision	Date:	9 th	March,	2021
----------	-------	-----------------	--------	------

Revision No. 2

Number of Pages: 5

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	: Dolphin Silicone Dashboard Polish
Recommended Use	: Dashboard Polish
Company Details	
Company Name	: Al Muqarram Industry L.L.C.
Address	: Etihad Street, Modern Industrial Area, Umm al Thaoob
	Post Box No. 24756, Umm Al Quwain, United Arab Emirates
Phone Number	: +971 (6) 5353796
Fax No.	: +971 (6) 5353964
E-mail ID	: info@muqarram.com
Website	www.mugarram.com

Emergency Telephone Number: 00971-549981925

2. HAZARDS IDENTIFICATION

Physical Hazards

Gases under pressure Flammable Aerosol

: Compressed Gas : Category 1

: Categor

Health Hazards

Serious eye damage Aspiration Hazard Specific target organ toxicity Single exposure

- : Category 2 A : Category 1
- : Category 3 narcotic effect

Label Elements



Other Hazards	
Precautionary Statements	: Keep away from heat / spark / open flames / hot surfaces.
Prevention	: No smoking. Do not spray on open flame or other ignition sources. Do not puncture or incinerate container. Do not breathe dust/fumes/gas/mist/vapors/spray.
Response	: If swallowed, immediately call a doctor. Do not induce Vomiting, remove person to fresh air. If in eyes, wash with water for several minutes.
Storage	: Store in a well- ventilated place. Keep container tightly closed. Do not expose to temperature exceeding 50°C.
Disposal	: Dispose of contents /containers in accordance with local, regional, and national regulation.

Head Office

AMI

info@muqarram.com

MSDS

www.muqarram.com







الـــــمكــــرم لــــصـــناعة المــــواد الــــعازلة ذ.م.م Al Muqarram Insulation Material Industry L.L.C.

3. COMPOSITION/INFORMATION ON INGREDIENT

Chemical Identity	CAS No	Weight %	Skin	Carcinogen
Silicone	Complex Mixture	10 - 15	No	No
Perfume	Complex Mixture	1-5	No	No
Propellant	74-98-6	20 – 30	No	No
Other ingredients	-	To 100%	No	No

4. FIRST AID MEASURES

Eyes	: Flush with large amount of cool running water for at least 15 minutes.
Ingestion	: If swallowed, do not induce vomiting. Never give anything by mouth to unconscious person.
Skin Contact	: Remove contaminated clothing. Wash affected area with soap and water.
Inhalation	: Remove victim to fresh air. Seek medical attention immediately. If breathing stops gives artificial respiration.
Most Important Symptoms	: May cause eye, skin, and respiratory irritation prolong skin contact may causes drying of skin. Inhalation may cause headache, dizziness, nausea, and other central nervous system depression. Aspiration into the lungs during ingestion or vomiting may cause lung damage.
Indication of Immediate Medical Attention and Special Treatment Needed	: Immediate medical attention is required.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media	: Dry chemical, CO2, sand, earth, water spray.
Specific Hazards Arising From	: Extremely flammable contents under pressure and can explode when exposed to heat
the Chemical	or flames. Vapors may cause flash fire.
Fire – Advice for Firefighters	: Firefighters must use standard protective equipment including fire-retardant gloves,
	coat, helmet with face shield, rubber boots.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment	: Ensure adequate ventilation especially in confined area, avoid contact with skin and
And emergency procedure	eyes.
Environmental Precautions	: Do not flushes into surface water or sanitary sewer system.
Containment and Clean Up	: Eliminate all ignition sources (no smoking, sparks, or flames in Immediate area). Keep
Procedures	combustibles (wood, paper, oil, etc.) Away from spilled materials. Stop the flow of material.
Method of cleaning up	: Absorbed waste maybe disposed as per local government regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling	: Handle with good industrial hygiene and safety practice avoid breathing vapors or mist. Avoid contact with eyes, clothing, and wash thoroughly after handling.
Proper Storage Condition	: Keep containers tightly closed in a cool, ventilated place. Keep away from sunlight, ignition sources. Do not expose to temperatures exceeding 50°C. Keep out of reach of children.

AMI

Head Office

💡 P.O. Box 24756, Sharjah, U.A.E. 🌜 +971 6 535 3796 ≤ info@muqarram.com ⊕ www.muqarram.com

info@muqarram.com

MSDS

www.muqarram.com

Page 2 of 5 AN ISO CERTIFIED COMPANY منع في الإمارات MADE IN UAE PRODUCT





الـــــمكــــرم لــــصـــناعة المــــواد الــــعازلة ذ.م.م Al Muqarram Insulation Material Industry L.L.C.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Identity	TWA			STEL	Carcinogen Category
Butane	PPM		mg/m ³	-	-
	800		1900	-	-
Respiratory Protectior Skin Protection Other Protective Equij Work/Hygienic Practic	oment	: Wea : Wea	ar protective gloves ar suitable protectiv	and protective clothing. e clothing such as apror	respiratory equipment. Is against splashing and contaminatior at the end of each work shift and

PHYSICAL AND CHEMICAL PROPERTIES 9.

Appearance	
Physical State	: Liquid
Form	: Aerosol
Color	: Clear/Colorless
Properties	
Odor	: Sweet odor (according to fragrance)
Solubility	: Non-soluble in water
Specific Gravity	: 0.7046
voc	: 182 g/L
Auto Ignition Temperature	: 410°C
Flash Point	: 52°C

10. STABILITY AND REACTIVITY

Stability	: Stable under normal temperature and recommended storage conditions.
Reactivity	: Stable under normal use.
Possibility of Hazardous	: No dangerous reaction known under condition of normal use.
Reaction	
Condition to Avoid	: Keep away from all the heat sources, open flames, and other sources of ignition.
In Complete Materials	: Strong oxidizing agent
Hazardous Decomposition Products	: Carbon Oxides

11. TOXICOLOGICAL INFORMATION

Possible Health Effect
Skin
Eye
Inhalation

- : May cause skin irritation and dermatitis. : Contact with eyes may cause irritation.
 - : May cause irritation of respiratory tract. May cause central nervous system depression with nausea, headache, and dizziness.

12. ECOLOGICAL INFORMATION

Eco-toxicity

AMI Head Office : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

MSDS info@muqarram.com www.muqarram.com

💡 P.O. Box 24756, Sharjah, U.A.E. 🌜 +971 6 535 3796

🐱 info@muqarram.com 🙂 www.muqarram.com

AN ISO CERTIFIED COMPANY منع في الإمارات MADE IN UAE

Page 3 of 5



AN ISO CERTIFIED COMPANY

PRODUCT

منع في الإمارات MADE IN UAE



الـــــمكــــرم لــــصـــناعة المــــواد الــــعازلة ذ.م.م Al Muqarram Insulation Material Industry L.L.C.

Persistence and Degradability
Bioaccumulation
Mobility
Other Adverse Effects

: No data available. : No information available. : Can disperses in water : No information available.

13. DISPOSAL CONSIDERATIONS

Water Treatment Method

: Disposal should be accordance with all local, state, provincial and federal regulation.

14. TRANSPORT INFORMATION

UN Number	: UN 1950
IMDG Shipping Name	: Aerosol
Transport Hazard Class	: 2.1
IATA Shipping Name	: Aerosol Flammable
IATA Hazard Class	: 2.1
UN Number	: UN 1950
ADG Shipping Name	: Aerosol
ADG Hazard Class	: 2.1
UN Number	: UN 1950

15. REGULATORY INFORMATION

TSCA	: Complies	
DSL/NDSL	: Complies	
ENCS	: Not determined	
IECSC	: Not determined	
Legend		
TSCA	: United State Toxic Substances Control Act Section 8 b Inventory.	
DSL/NDSL	: Canadian Domestic Substances List/Nondomestic Substances list.	
ENCS	: Japan existing and New Chemical Substances.	
IECSC	: China Inventory of Existing Chemical Substances	
KECL	: Korean Existing and Evaluated Chemical Substances.	
PICCS	: Philippines Inventory of Chemicals & Chemical Substances.	
AICS	: Australian Inventory of Chemical Substances.	
CERCLA	: Comprehensive Environmental Response, Compensation, and Liability Act.	
DOT	: Department of Transportation	
FIFRA	: Federal Insecticide, Fungicide, and Rodenticide Act	
HMIRC	: Hazardous Materials Information Review Commission	
HMIS	: Hazardous Materials Identification System	
NFPA	: National Fire Protection Association	
NIOSH	: National Institute for Occupational Safety and Health.	
Full Text of H-statements		
H 225	: Highly Flammable liquid.	
H 226	: Flammable liquid and Vapor.	
H 280	: Contains gas under pressure may explode if heated.	
H 301	: Toxic if swallowed.	
Н 304	: May be fatal if swallowed and enter airways.	
H 311	: Toxic in contact with skin.	
H 312	: Harmful in contact with skin.	
H 315	: Causes skin irritation.	
H 319	: Causes serious eye irritation.	

Head Office

💡 P.O. Box 24756, Sharjah, U.A.E. 🌜 +971 6 535 3796 ≤ info@muqarram.com ⊕ www.muqarram.com





الـــــمكــــرم لــــصـــناعة المــــواد الــــعازلة ذ.م.م Al Muqarram Insulation Material Industry L.L.C.

H 331	: Toxic if inhaled.
Н 332	: Harmful if inhaled.
Н 370	: Causes damage to organ.
Н 373	: May cause damage to organ through prolonged exposure.

16. OTHER INFORMATION

General Information

This product should be used as directed. For further information, please consult product data sheets and application information bulletin for this product.

Further Information

The information contained herein is based on the present state of our knowledge. It characterizes the product about the appropriate health and safety precaution, and hazard information. It does not represent a guarantee of the properties of product.

Revision Comments

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is correct.

17. DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated.

However, no warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

www.muqarram.com

info@muqarram.com

