

# TECHNICAL DATA SHEET

## DOLPHIN AM-40 ANTI RUST LUBRICANT

Revision Date: 12<sup>th</sup> Nov 2019

Revision No: 01

Number of Pages: 2

### PRODUCT DESCRIPTION

**Dolphin AM-40 Anti-Rust Lubricant** provides superior quality lubrication and rust protection to all metals subjected to rust/corrosion. It exhibits the property to infiltrate the surface rust instantly.

### TECHNICAL PROPERTIES



Properties	Specifications
Appearance	Transparent Liquid
Odor	Characteristic
Density @ 25°C	0.81 + 0.02 g/cm <sup>3</sup>
Solubility in Water	Insoluble
Flash Point	45°C

Performance	
Average Film Thickness	4 – 12 µm
Dry to Touch Time	Not applicable
Reapplication Period Outdoors	6 – 12 months
Reapplication Period Indoors	2 years

(Information on this data sheet is subject to change without prior notice and should not be used for writing specifications)

### KEY FEATURES

- Easy to Apply
- Provides instant and long-lasting result
- Protects Metal Tools and Machinery from rusting/corrosion, without damaging the surface
- Serves dual-purpose; rust protector and lubricator

<b>Directions for use</b>	<ul style="list-style-type: none"> <li>• Shake Can well before spraying</li> <li>• Spray the material evenly on the desired surface and leave it for 30 minutes</li> <li>• Clean the application area with cotton cloth</li> </ul>
<b>Packaging</b>	<p><b>Dolphin AM-40 Anti Rust Lubricant</b> is available in:</p> <ul style="list-style-type: none"> <li>• 220 ML (24 pcs/carton)</li> <li>• 400 ML (12pcs/carton)</li> <li>• 480 ML (24pcs/carton)</li> </ul>



WORLD-CLASS  
CHEMICALS

<b>Storage and shelf life</b>	Store in a cool, dry location in unopened containers at temperature below 50°C. Do not place in direct sunlight or nearby any heat and flame source. Do not expose to temperature exceeding 50°C.  <b>Dolphin AM-40 Anti Rust Lubricant</b> has a shelf life of 36 months from date of manufacturing.
<b>Handling precautions</b>	Contents extremely flammable. Do not smoke while spraying. Do not use near open flames. Do not puncture or incinerate even after use. Exposure to high temperatures may cause can burst. Keep away from all live electrical sources including battery terminals, electrical panels, and other electrical components. For safe handling information, refer to the Material Safety Data Sheet of this product.

KEEP OUT OF REACH OF CHILDREN • KEEP CONTAINER TIGHTLY CLOSED • FOR INDUSTRIAL & PROFESSIONAL USE

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.