



WORLD-CLASS CHEMICALS

# TECHNICAL DATA SHEET

## DOLPHIN FLOOR ADHESIVES

Revision Date: 12<sup>th</sup> March 2020

Revision No: 02

Number of Pages: 2

## PRODUCT DESCRIPTION

Dolphin Floor Adhesives is based on premium quality synthetic resin, additives, tackifier, and fine grade mineral fillers. It is acrylic water-based adhesive and compatible with most of the substrates.

## TECHNICAL PROPERTIES



Properties	Specifications
Color	Cream
Appearance	Smooth Paste
Open Time (mins)	20 to 30 (depending on ambient temperature, substrate & application)
Curing Time (Hrs)	48 (Approx.)
Specific Gravity	1.20 ± 0.15 g/cm <sup>3</sup>
Viscosity @ 25°C (S#6, RPM#10) CPS	20000 to 25000
Solid Content (%)	65 ± 5
Coverage (0.1-0.2mm wet film thickness)	850 grams/m <sup>2</sup> (depending on type of surface and application)
Shelf Life (Months)	12

Note:

\* Curing time (Skin Over Time & Tack Free Time) may vary depending on climatic condition during application.

(Information on this data sheet is subject to change without prior notice and should not be used for writing specifications)

## TYPICAL USES

- Multi-Purpose Floor & PVC Vinyl Adhesion
- Bonding of PVC sheet, Vinyl coverings and tiles, EPDM sheet, Polystyrene board, PU foam and similar material with concrete, metals, and wooden substrates
- Bonding substrate with porous and non-porous surfaces
- Floor heating installations. However, the heating should be switched off at least 48 hours before and after the installation of floor coverings

## KEY FEATURES

- Environmentally safe
- Easy application
- Quick setting
- Suitable to most of the surfaces
- Good coverage
- Heat resistant
- Non-Flammable
- Water resistance

### Preparation

The surface must be leveled, sound, dry and clean (accordingly to BS 8203).

### Application Instruction

Application surface should be dry and dust, rust, and grease-free. Stir well before use. Apply the adhesive uniformly on the substrate using a fine trowel, brush or roller and wait for 15-20 minutes for adhesive to become tacky and then lay the floor covering. Bonding over existing floor coverings should be avoided. Clean any excess adhesive with water immediately.



WORLD-CLASS  
CHEMICALS

<b>Coverage</b>	Coverage depends upon the nature of the surface to be applied. On average, smooth surface will give First Coat - 850 gm/sq. mtr.
<b>Packaging</b>	<b>Dolphin Floor Adhesives</b> is available in 5 kg bucket, 10 kg bucket and 20 kg bucket.
<b>Storage and shelf life</b>	Store away from sunlight and preferably below 30°C. Storage should be frost protected. <b>Dolphin Floor Adhesives</b> has 12 months shelf life if stored in required conditions.
<b>Shipping limitations</b>	None
<b>Health and safety</b>	As with all chemicals, caution should always be exercised. Protective clothing such as gloves and goggles should be worn. Inhalation of vapor or mist should be avoided. If inhaled symptoms include coughing, wheezing, laryngitis, and shortness of breath, headache, nausea, and vomiting. Immediately shift victim to fresh air, and, if needed immediately start artificial respiration. Give oxygen if breathing is labored. Get emergency medical help. In case of eye contact, flush eyes with water for 15 minutes and call for medical help. Ingestion causes nausea, vomiting, and loss of consciousness. If accidentally swallowed do not induce vomiting rather call for medical help immediately. For skin contact, flush with water or soap and water until all traces have been removed. Seek medical attention if required.

KEEP OUT OF REACH OF CHILDREN • KEEP CONTAINER TIGHTLY CLOSED • FOR INDUSTRIAL & PROFESSIONAL USE

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.