

TECHNICAL DATA SHEET

DOLPHIN STARTING FLUID

Revision Date: 1st April 2023

Revision No: 0

Number of Pages: 2

PRODUCT DESCRIPTION

Dolphin Starting Fluid is suitable for the easy and safe starting of combustion engines. The safe cold starting of all engines is made possible by a special combination of ingredients. Dolphin Starting fluid is ideal at low temperatures, in damp weather or after long engine downtimes. The spray protects both engine and the battery. Dolphin Starting fluid is suitable for both diesel and petrol engines. Whether with or without a catalytic converter, whether a motor vehicle or construction machinery, agriculture machinery, chain saws, lawn mowers, boat engines, motorcycles, or scooters – Dolphin Starting fluid can be used everywhere.

TECHNICAL PROPERTIES



Properties	Specifications
Appearance	Clear to Orange
Features	For all combustion engines
Odour	Solvent
Silicone Free	Yes
Physical State	Liquid
Specific Gravity	0.790 – 0.820

(Information on this data sheet is subject to change without prior notice and should not be used for writing specifications)

KEY FEATURES

- Enables quick starting of petrol and diesel engines.
- Prevents battery fatigue.
- Especially effective with cold starts during cold or wet seasons prevents carburetors from freezing.
- Applies easily.
- The special valve of the aerosol allows to use it in all positions and to empty it completely.



WORLD-CLASS
CHEMICALS

Directions for use	<ul style="list-style-type: none"> • Shake can before use. • Dolphin Starting fluid spray directly into the air inlet or onto the air filter, wait briefly and start engine slowly. The use of choke or preheating the diesel engines is not required. • Repeat the process.
Packaging	Dolphin Starting fluid is available in 450 ML Aerosol can.
Storage and shelf life	<p>Pressurized container Store in a dry and well-ventilated storeroom, protect from sunlight and do not expose to temperature above +40 °C. Do not keep or expose it to heat or flame.</p> <p>Dolphin Starting fluid has a shelf life of 36 months from date of manufacturing.</p>
Handling Precautions	<p>Avoid contact with eyes and skin. In case of eye contact, immediately flush with plenty of water and take medical advice. Keep out of reach children.</p>

KEEP OUT OF REACH OF CHILDREN • KEEP CONTAINER TIGHTLY CLOSED • FOR INDUSTRIAL & PROFESSIONAL USE

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. AMI reserves the right to change the properties of its products without notice.

